



Water Closet & Flushometer Combo

WETS-2760.3005-1.28-CP

Product description

1.28 gpf, Polished Chrome Finish, 1.5" Flush Connection, Fixture Connection Rear Spud, Single Flush, Integrated Control Stop, Electrical Override, Battery with Hardwired Option, Short V500A & Adjustable Flush Connection Vacuum Breaker, Front Accessible Wall Box, ST-2469-STG Water Closet and CX 8158 Flushometer.

Compliances & Certifications



(BAA Compliant, BABAA Compliant)

Code 27603005

Downloads

- [ST-2469 Installation Instructions.pdf](#)
- [CX 8158_8198 Installation Instructions.pdf](#)
- [CXSensor.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Flush Volume: 1.28 gpf (4.8 lpf)

Features

- Fixed volume piston with filtered O-ring bypass
- Front access wall plate requires no rear access plumbing chase
- Sensor activated, hands-free operation
- Battery operated with hardwired option
- Electronic override button
- Low battery indicator light
- Vandal resistant wall plate
- Adjustable flush connection
- 8-1/2" (W) x 9-1/4" (H) Wall Box Panel Dimension
- Designed to maximize and complement Sloan flushometers
- Universal model works with Sloan flushometers from 1.1 to 1.6 gpf
- Durable, hygienic vitreous china construction with elongated rim
- Syphon jet flushing achieves 1000g Map Scores when used with Sloan flushometers
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- Meets ADA guidelines and ANSI A117.1 requirements when installed accordingly
- Permanent SloanTec® hydrophobic antimicrobial glaze inhibits the growth and buildup of germs, bacteria, mold, mildew and mineral scale on the surfaces

Components

- Flushometer: Code 3400301
- Water Closet: Code 2172469

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

