



Act-O-Matic® Showerhead

AC-460-2.5GPM-CP

Product description

Polished Chrome Finish, Act-O-Matic® Institutional Behind the Wall Installation Showerhead.

Compliances & Certifications



(ASME A112.18.1 Compliant, BAA Compliant, BABAA Compliant, CEC Compliant, IAPMO listed ASME)

Code 4024600

Finish

 Polished Chrome (CP)

Downloads

- [AC 450_460 Installation Instructions.pdf](#)
- [Showerhead Parts and Accessories Repair and Maintenance Guide.pdf](#)
- [Programmed Water Technologies \(PWT\) Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Finish: Polished Chrome (CP)
- Flow Rate: 2.5 gpm (9.5Lpm) (2.5GPM)
- Self Cleaning: Yes

Features

- Institutional Style Shower Head
- Designed for secure, in-wall installation (behind the wall access required for installation)
- Spring-loaded, self-cleaning spray disk prevents particle clogging and reduces maintenance
- “Cone within a cone” spray pattern for total body coverage
- All brass construction
- 1/2” IPS inlet
- Fast drain feature to prevent residual slow dripping
- Shower Head shall be in conformance to all requirements of ANSI/ASME Standard A112.18.1M, CSA B-125 and the United States Federal Energy Policy Act.
- Polished Chrome Finish
- Adjustable spray angle with pressure compensating 2.5 gpm (9.4 Lpm) flow control
- Mounting Plate with Vandal Resistant Mounting Screws

Recommended specifications

Sloan Act-O-Matic Institutional Showerhead model no. AC-460 2.5 gpm. Vandal Resistant and Chrome Plated.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

