

OPTIONS**Flush Volume**

- 1.0 gpf (3.8 Lpf) (1.0)
- 1.5 gpf (5.7 Lpf) (1.5)

Water Efficiency

- Low Consumption
- Water Saver

L Dimension

- 3 ¾" (95mm) (3-3/4-LDIM)
- 6 ¾" (171mm) (6-3/4-LDIM)
- 7 ¾" (197mm) (7-3/4-LDIM)
- 10 ¾" (273mm) (10-3/4-LDIM)
- 12 ¾" (324mm) (12-3/4-LDIM)
- 4 ¾" (121mm) (4-3/4-LDIM)
- 5 ¾" (146mm) (5-3/4-LDIM)

Wall Box

- Standard (not included, order separately)

Push Button

- Metal Index (L)

Control Stop

- Ground Joint (GJ)

Vacuum Breaker

- Less (XYV)

Compliances & Certifications

- BAA Compliant
- BABAA Compliant
- ADA Compliant

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard NAVAL 195 shown

DESCRIPTION

Naval Concealed Manual Urinal Flushometer

FEATURES

- Factory set flush volume of 1.0 gpf/3.8 Lpf has an adjustable range of 0.5 gpf/1.7 Lpf to 3.0 gpf/11.4 Lpf
- Non-hold-open oscillating handle, Bak-Chek™ control stop and self-cleaning Xpelor Metering By-Pass ensure reliable operation and accurate flush delivery
- Available with adjustable or ground joint supply stop (ground joint recommended for salt water applications)
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Naval Piston Type Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Naval Repair and Maintenance Guide](#)
- [Additional Downloads](#)