



BASYS® Sensor Faucet

EFX-277

Product description

BASYS® Solar-Powered Deck-Mounted Mid Body Guided Handwashing Display Faucet.

Compliances & Certifications



(ASME A112.18.1 Compliant, BREEAM Materials Credit, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, EPD, GPC 0.25 or less, Green Globes Credit, Green Globes Water, HPD, LEED Credit, LEED HPD, LEED Water, NYC604.4, Proposition 65, Satisfies LEED Credits, TAS, WELL Building Standard)

Listed compliances and certifications may vary based on product variation.

Finish



Available in Polished Chrome (CP).

Downloads

- [EFX 1Xx_2Xx Installation Instructions](#)
- [EFX 1Xx_2Xx \(SP\) Installation Instructions](#)
- [Trim Plate Guide](#)
- [IR FAQs Repair and Maintenance Guide](#)
- [Faucet and Soap Dispenser Brochure](#)
- [Additional Downloads](#)

Videos

- [BASYS® Guided Handwashing Faucets](#)
- [BASYS® Faucet Installation and Features](#)
- [Sloan Connect App®](#)

Features

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature
- Single hole installation
- Includes all mounting hardware
- Line purge mode, eliminates stagnant water
- Adjustable time-outs
- 3 year limited warranty


Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Compatible products



ESD-500

[View product >](#)