**Standard Washdown Urinal**

# SU-1009

## Product description

Standard, Vitreous China Washdown Urinal.

## Compliances & Certifications

(ADA Compliant, BREEAM Materials Credit, CalGreen Compliant, CEC Compliant, cUPC Green Certified, EPD, Green Globes Credit, HPD, IAPMO, LEED Credit, LEED HPD, Satisfies LEED Credits, EPA WaterSense Listed)

**Code 1101009**

## Downloads

- Standard Spud Urinal Installation Instructions.pdf
- SS:ST:SU:WETS:WEUS Fixtures Repair and Maintenance Guide.pdf
- Fixture Brochure.pdf
- Additional Downloads

## Videos

- Sloan – Company Overview

## Details

- Flush Volume: 0.125-1.0 gpf (1.9-3.8 lpf)
- Flush Volume determined by the Flushometer used with the Fixture
- Nominal Dimensions: 14.25” x 17.25” x 25.5” (362 x 438 x 648mm)
- Flush Method: Washdown

## Features

- Designed to maximize and complement Sloan flushometers
- Universal high-efficiency model works with 0.125, 0.25 and 0.5 gpf Sloan flushometers
- Thorough washdown flushing action
- Durable, hygienic vitreous china construction
- Vandal resistant stainless steel strainer included
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- Water Sense listed by EPA that qualifies for most rebate programs
- Meets ADA guidelines and ANSI A117.1 requirements when installed accordingly

## Plumbing System Requirements

- Maximum Static Pressure: 80 PSI (552 kPa)
- Maximum Flow Rate: 8.5 gpm (32.2 Lpm)

## Warranty

View Warranty Information

## Notes

All information contained within this document subject to change without notice.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

WaterSense compliant when used with a WaterSense compliant flushometer.

Find a compatible flushometer for this urinal.

2 1/4"
(57 mm)
3/4" Top Spud
20 3/4"
(527 mm)
(Centerline
of outlet)
Centerline
of outlet
to floor
19" (483 mm)
(12" for ADA)
14 1/4"
(362 mm)
Finished Wall
Finished Floor
15 5/8" (397 mm)
12"
(305 mm)
Mounting Hole
Center
18"
(457 mm)
24"
(610 mm)
(17" for ADA)
16"
(406 mm)
Centerline
of outlet to floor
19" (483 mm)
(12" for ADA)
17 1/4" (438 mm)
Finished Floor