



Optima® Sensor Faucet

EAF-300-HLT-GR-0.5GPM-AER-FCT

Product description

Hardwired Less Transformer Power Supply, Mixer Not Included, Graphite Finish, 0.5 gpm, Aerated Spray, Infrared Sensor, Optima® Hardwired-Powered Deck-Mounted Mid Body Faucet.

Compliances & Certifications



(ASME A112.18.1 Compliant, BREEAM Materials Credit, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, EPD, Green Globes Credit, Green Globes Water, HPD, LEED Credit, LEED HPD, NSF-61/CAN-61, NYC604.4, Satisfies LEED Credits, TAS, WELL Building Standard)

Code 33351252

Finish



Graphite (GR)

Downloads

- [EAF 3X0 Installation Instructions.pdf](#)
- [Faucet Spray Heads Maintenance Guide.pdf](#)
- [Trim Plate Guide.pdf](#)
- [Optima Plus EAF 3X0 Repair and Maintenance Guide.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Product Information

Details

- Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM)
 - Spray Type: Aerated (AER)
 - Sensor Type: Infrared
 - Mounting Type: Single Hole
 - Power Supply: Hardwired Less Transformer (HLT)
 - Temperature Mixer: Mixer Not Included
 - Finish: Graphite (GR)
 - Factory Default Timeout: 15s
 - Factory Default GPC: 0.083 gpc
-

Features

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Double Infrared Sensor with Automatic Setting Feature and Microprocessor
- Bi-Stable Magnetic Solenoid Valve (for increased energy savings)
- Water Supply Connection with Flexible High-Pressure Hose and Strainer
- 6 Volt DC Plug-in Adapter (must be ordered separately for Less transformer (-LT) faucets)
- Daisy Chain Electrical Splitter Cable included with Less transformer (-LT) faucets
- IR-Click feature permits activation of continuous run and temporary off modes
- Appropriate Mounting Hardware included
- 3 year limited warranty
- PVD Graphite Finish
- 0.5GPM sprayhead with aerated flow pattern
- AC Powered faucet less transformer (-LT), includes daisy chain connector for connecting up to 6 faucets.

EAF-300-HLT-GR-0.5GPM-AER-FCT

Electrical specifications

- Sensor Range: 4" -5" (102-127 mm)
-

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the EAF-300 product? [View the general spec sheet with all options.](#)

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet

