


# Masonry & Concrete Screws

Pan Head



## Rapid & Effective Masonry & Concrete Screws



Ideal for fitting

- Hand rails
- Shelf brackets
- Security lighting
- Metal straps banding

Countersunk



Non-expansion  
for close to  
edge fixing



Serrated  
V-threads  
for optimum  
insertion



High-low start  
threads for  
rapid pick up

## Masonry Screw - Countersunk


Zinc



TX DRIVE



CONCRETE BRICK




BLOCK WOOD



ALL STEEL  
NON-FLAMMABLE  
FIXING

- Light duty fixing ideal for ironmongery handrails & brackets
- TX25 TX Drive recess reduces wear & camming out
- Serrated V-threads to achieve optimum insertion
- Conforms to BS 7671



100-150KG

### Technical Data

| Substrate                  | Concrete $\geq 25\text{N/mm}^2$ |      |
|----------------------------|---------------------------------|------|
| Length (mm)                | 40-80                           | 100  |
| Drill Hole Ø (mm)          | 5.0                             | 5.0  |
| Min. Embedment Depth (mm)  | 25                              | 37   |
| Min. Drill Hole Depth (mm) | 35                              | 47   |
| Rec. Tensile Load (kN)     | 1.00                            | 1.50 |
| Max Rec. Load (kg)         | 100                             | 150  |

| Product Code              | Size (mm) | Driver Bit Size | Max. Fixture Thickness (mm) | Fixture Clearance Hole Ø (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|---------------------------|-----------|-----------------|-----------------------------|-------------------------------|----------------|--------------------|--------------------|
| BOX (DRIVER BIT INCLUDED) |           |                 |                             |                               |                |                    |                    |
| 640MFCSK                  | 6.0 x 40  | TX25            | 15                          | 6.5                           | 100            | 18                 | 648                |
| 660MFCSK                  | 6.0 x 60  | TX25            | 35                          | 6.5                           | 100            | 12                 | 432                |
| 680MFCSK                  | 6.0 x 80  | TX25            | 55                          | 6.5                           | 100            | 12                 | 432                |
| 6100MFCSK                 | 6.0 x 100 | TX25            | 63                          | 6.5                           | 100            | 10                 | 360                |

CON04

### TIMPAC

|        |           |      |    |     |    |    |      |
|--------|-----------|------|----|-----|----|----|------|
| 725157 | 6.0 x 40  | TX25 | 15 | 6.5 | 12 | 10 | 6000 |
| 725375 | 6.0 x 60  | TX25 | 35 | 6.5 | 10 | 10 | 6000 |
| 725010 | 6.0 x 80  | TX25 | 55 | 6.5 | 8  | 10 | 6000 |
| 725863 | 6.0 x 100 | TX25 | 63 | 6.5 | 6  | 10 | 6000 |

PAK43

## Masonry Screw - Pan Head


Zinc



TX DRIVE



CONCRETE BRICK



BLOCK WOOD



ALL STEEL  
NON-FLAMMABLE  
FIXING

- Light duty fixing ideal for ironmongery
- TX25 TX Drive recess reduces wear & camming out
- Serrated V-threads to achieve optimum insertion
- Conforms to BS 7671



100-150KG

### Technical Data

| Substrate                  | Concrete $\geq 25\text{N/mm}^2$ |      |
|----------------------------|---------------------------------|------|
| Length (mm)                | 40-80                           | 100  |
| Drill Hole Ø (mm)          | 5.0                             | 5.0  |
| Min. Embedment Depth (mm)  | 25                              | 37   |
| Min. Drill Hole Depth (mm) | 35                              | 47   |
| Rec. Tensile Load (kN)     | 1.00                            | 1.50 |
| Max Rec. Load (kg)         | 100                             | 150  |

| Product Code              | Size (mm) | Driver Bit Size | Max. Fixture Thickness (mm) | Fixture Clearance Hole Ø (mm) | Pack Qty (pcs) | Carton Qty (packs) | Pallet Qty (packs) |
|---------------------------|-----------|-----------------|-----------------------------|-------------------------------|----------------|--------------------|--------------------|
| BOX (DRIVER BIT INCLUDED) |           |                 |                             |                               |                |                    |                    |
| 640MFAN                   | 6.0 x 40  | TX25            | 15                          | 6.5                           | 100            | 18                 | 648                |
| 660MFAN                   | 6.0 x 60  | TX25            | 35                          | 6.5                           | 100            | 12                 | 432                |
| 680MFAN                   | 6.0 x 80  | TX25            | 55                          | 6.5                           | 100            | 16                 | 576                |
| 6100MFAN                  | 6.0 x 100 | TX25            | 63                          | 6.5                           | 100            | 10                 | 360                |

CON05

### TIMPAC

|        |          |      |    |     |    |    |      |
|--------|----------|------|----|-----|----|----|------|
| 725500 | 6.0 x 40 | TX25 | 15 | 6.5 | 12 | 10 | 6000 |
| 725997 | 6.0 x 60 | TX25 | 35 | 6.5 | 10 | 10 | 6000 |

PAK44