

# Declaration of Performance

No. DOP-04-AHS-01-S2067 / Page 1 of 4

## 9 in 1 Universal Adhesive & Sealant



1. Unique identification code of the product type:

**TIMCO 9 in 1 Universal Adhesive & Sealant**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see product packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**EN 15651-1:2012**

**Sealants for façade elements (F)**

Type: **F-EXT-INT-CC (Class 25HM)**

Non-structural facade sealant intended for sealing exterior wall joints, window and door perimeter joints in building construction, including the interior face.

**EN 15651-3:2012**

**Sealants for joints in sanitary environments (S)**

Type: **S (Class XS3)**

Sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurized water.

It covers joints in:

- Bathroom
- Toilets
- Showers
- Domestic kitchens

**EN 15651-4:2012**

**Sealants for pedestrian walkways (PW)**

Type: **PW-EXT-INT-CC (Class 25HM)**

Cold applied non-structural elastic sealants used for movement joints in floors in building construction for the interior and the exterior use.

Areas of application are: floor joints for pedestrian walkways, public areas, movement joints between concrete slabs, areas with pedestrian load, areas used with trolleys, walkable floors, balconies, terraces, warehouses.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

T. I. Midwood & co. Ltd.  
Green Lane, Wardle, Nantwich, Cheshire, CW5 6BJ

# Declaration of Performance

No. DOP-04-AHS-01-S2067 / Page 2 of 4

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 for type of testing  
System 3 for the reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body: **SKZ - TeConA GmbH (1213)**, performed the initial testing according to **EN 15651-1 / EN 15651-3 / EN 15651-4** and reaction to fire under System 3 and issued a: **test report**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance

**EN 15651-1:2012 Type: F-EXT-INT-CC**  
Conditioning: **Procedure B (according to ISO 8340)**  
Substrate: **Mortar M1 (with primer P03)**  
**Glass (without primer)**  
**Anodised aluminium (without primer)**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD (*)	EN 15651-1:2012
Water tightness and air tightness:		
Resistance to flow	≤ 3	EN 15651-1:2012
Loss of volume	≤ 10%	EN 15651-1:2012
Tensile properties at maintained extension after water immersion	NF	EN 15651-1:2012
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	EN 15651-1:2012
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	EN 15651-1:2012
Durability	Pass	EN 15651-1:2012

(\*) See material safety data sheet | NPD = No performance determined | NF=No failure | NR=Not required

# Declaration of Performance

No. DOP-04-AHS-01-S2067 / Page 3 of 4

**EN 15651-3:2012 Type: S**

**Conditioning: Procedure B (according to ISO 8340)**

**Substrate: Glass (without primer)  
Anodised aluminium (without primer)**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD (*)	EN 15651-3:2012
Water tightness and air tightness:		
Vertical flow resistance	≤ 3	EN 15651-3:2012
Loss of volume	≤ 20%	EN 15651-3:2012
Tensile properties at maintained extension after water immersion	NF	EN 15651-3:2012
Microbiological growth	3	EN 15651-3:2012
Durability	Pass	EN 15651-3:2012

**EN 15651-3:2012 Type: S**

**Conditioning: Procedure B (according to ISO 8340)**

**Substrate: Mortar M1 (with primer P03)**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD (*)	EN 15651-3:2012
Water tightness and air tightness:		
Tensile properties at maintained extension	NF	EN 15651-3:2012
Loss of volume	≤10%	EN 15651-3:2012
Tear resistance	NF	EN 15651-3:2012
Adhesion / cohesion properties at maintained extension after 28 days water immersion	≤50%	EN 15651-3:2012
Adhesion / cohesion properties at maintained extension after 28 days salt water immersion	NF	EN 15651-3:2012
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	EN 15651-3:2012
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	EN 15651-3:2012
Durability	Pass	EN 15651-3:2012

(\*) See material safety data sheet | NPD = No performance determined | NF=No failure | NR=Not required

Where pursuant in Article 37 or 38 the Specific technical documentation had been used, the requirement with which the product complies: not relevant.


# Declaration of Performance

No. DOP-04-AHS-01-S2067 / Page 4 of 4

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Simon Midwood

Managing Director

TIMCO House  
2021

Name

Position

Signature

Location &amp; Date