



C2 FLOOR-FIX PREMIUM SCREW

DESIGNED FOR FIXING FLOORBOARDS TO JOISTS

Ideal for: Hardwood | Softwood | Man-Made Board



DESIGNED FOR SUPERIOR HOLD



STOPS THE BOARDS JACKING



PRECISION TX DRIVE PREVENTS "CAM-OUT"



C2 TONGUE-FIX PREMIUM SCREW

DESIGNED FOR FIXING TONGUE & GROOVE FLOORBOARDS & PANNELLING

Ideal for: Hardwood | Chipboard | Softwood



DESIGNED FOR SUPERIOR HOLD



HIDDEN FIXING SYSTEM



PRECISION TX DRIVE PREVENTS "CAM-OUT"

Yellow



A specialised fastener designed to securely fix and clamp floorboards to joists. C2 is a revolutionary high-performance screw designed using modern manufacturing methods and an innovative twin-cut point, ensuring consistent and rapid pick-up while reducing timber splitting.

- Specifically designed dual action head - finishing teeth and self-countersinking ribs ensures a flush finish
- Plain shank for pulling the two substrates together without manual clamping
- Coated with a high-molecular polymer lubricant that reduces the insertion torque by up to 52% and increases rust protection up to 20 times longer than a standard zinc plating
- Dual angle thread for ultimate performance and exceptionally high pull-out resistance
- Patented twin cut technology for rapid "pick-up" and reduces timber splitting

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
42055C2MDFB	4.2 x 55	TX20	200	15	540 CC204
TUB (DRIVER BIT INCLUDED)					
42055C2MDF	4.2 x 55	TX20	250	12	360 CC204

Yellow



A specialised fastener for fixing tongue and groove floorboards and panelling. It creates a secure and hidden fixture, allowing for a flush fit with the next board. C2 is a revolutionary high-performance screw designed using modern manufacturing methods and an innovative twin-cut point, ensuring consistent and rapid pick-up while reducing timber splitting.

- Reduced head for concealed countersinking
- Plain shank for pulling the two substrates together without manual clamping
- Coated with a high-molecular polymer lubricant that reduces the insertion torque by up to 52% and increases rust protection up to 20 times longer than a standard zinc plating
- Dual angle thread for ultimate performance and exceptionally high pull-out resistance
- Patented twin cut technology for rapid "pick-up" and reduces timber splitting

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
35045C2TGBX	3.5 x 45	TX10	200	50	1200 CC203
TUB (DRIVER BIT INCLUDED)					
35045C2TG	3.5 x 45	TX10	350	20	600 CC203