

Technical Data Sheet

Ref: TDS-06-BMW-21

Builders Metal Work

Fixing Bands - Galv & Stainless Steel

Features

- A versatile multi purpose banding that can be cut, bent and formed for all types of light application.
- Ideal for DIY, industrial and agricultural uses.
- Multiple hole sizes to add to its versatility.
- Stainless steel must be used where there is corrosive environment and/or the base material has inherent corrosive characteristics e.g. Green Oak.
- Galvanised steel.
- Available in black and white PVC coating.
- Grade 1.4301 austenitic stainless steel to EN10088-2.

Dimensional Data

Product Code	Length (m)	Width (mm)	Thickness (mm)	Large Hole Ø (mm)	Small Hole Ø (mm)
1210FB	10	12	0.8	5.0	2.5
1810FB	10	18	0.8	6.5	3.0
2510FB	10	25	1.0	9.0	4.0

Product Code	Length (m)	Width (mm)	Thickness (mm)	Hole Ø (mm)	Colour
1210FBWHITE	10	12	0.7	5	White
1210FBLACK	10	12	0.7	5	Black

Product Code	Length (m)	Width (mm)	Thickness (mm)	Round Holes Ø	Square Holes
2010FBS*	10	20	0.7	3.75 & M10	M8 & M10

*Stainless Steel.

All stated figures (mm) are approx and for reference only.

Installation Guidelines

- Always ensure that compatible corrosion resistant fixings are used, i.e. do not use galvanised fixings with stainless steel products or vice versa.
- Use appropriate fixings.