

# Declaration of Performance

No. DOP-04-AHS-02-S2082 / Page 1 of 3

## 9 in 1 Universal Adhesive & Sealant - Crystal Clear



1. Unique identification code of the product type: **TIMCO 9 in 1 Universal Adhesive & Sealant - Crystal Clear**
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): **Batch number: see product packaging**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**EN 15651-1:2012**  
**Type: F-EXT-INT Class 7,5P**  
Non-structural facade sealant intended for sealing exterior wall joints, window and door perimeter joints in building construction, including the interior face.  
**EN 15651-3:2012**  
**Type: S Class S 1**  
Sealant used for sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurised water. It covers joints in: bathrooms, toilets, showers, domestic kitchens.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): **T. I. Midwood & co. Ltd.**  
**Green Lane, Wardle, Nantwich, Cheshire, CW5 6BJ**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not relevant**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 3 for type of testing**  
**System 3 for the reaction to fire**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: **The notified body Tecnalía (1292)**  
**Performed the determination of the product-type on the basis of type testing under system and issued: a test report.**

# Declaration of Performance

No. DOP-04-AHS-02-S2082 / Page 2 of 3

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not relevant**

9. Declared performance

**EN 15651-1:2012 Type: F-INT**

**Conditioning: Method A**

**Substrate: Glass (without primer)**

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501-1:2007+A1	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD (*)	EN 15651-1:2012;4.5	EN 15651-1:2012
<b>Water tightness and air tightness:</b>			
Resistance to flow	< 3	Modified EN ISO 7390	EN 15651-1:2012
Loss of volume	< 10%	EN ISO 10563	EN 15651-1:2012
Tensile properties: elongation at break at 23°C	NF	EN ISO 10591	EN 15651-1:2012
Tensile properties (i.e. elongation): at maintained extension after water immersion	NF	EN ISO 10590	EN 15651-1:2012
Tensile properties (i.e. secant modulus): for non-structural low modulus sealants used in joints in cold climate areas (-30°C)		Modified EN ISO 8339	EN 15651-1:2012
Tensile properties (i.e. at maintained extension): for non-structural sealants used in joints in cold climate areas (-30°C)		Modified EN ISO 8340	EN 15651-1:2012
Durability	Pass	EN ISO 10591 modified EN ISO 8339 EN ISO 8340	EN 15651-1:2012

(\*) See product safety data sheet | NPD = No performance determined | NF=No failure

# Declaration of Performance

No. DOP-04-AHS-02-S2082 / Page 3 of 3

9. Declared performance

**EN 15651-1:2012 Type: F-EXT-INT**

Conditioning: **Method A**

Substrate: **Glass (without primer)**


Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN 13501-1:2007+A1	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD (*)	EN 15651-1:2012;4.5	EN 15651-1:2012
Water tightness and air tightness:			
Resistance to flow	< 3	Modified EN ISO 7390	EN 15651-1:2012
Loss of volume	< 10%	EN ISO 10563	EN 15651-1:2012
Tensile properties: elongation at break at 23°C	NF	EN ISO 10591	EN 15651-1:2012
Tensile properties (i.e. elongation): at maintained extension after water immersion	NF	EN ISO 10590	EN 15651-1:2012
Microbiological growth	1	EN ISO 846:1997, procedure B	EN 15651-1:2012
Durability	Pass	EN ISO 10591 EN ISO 10590	EN 15651-1:2012

(\*) See product safety data sheet | NPD = No performance determined | NF=No failure

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Simon Midwood

Managing Director



TIMCO House  
2021

Name

Position

Signature

Location & Date