


Straight Band & Hook on Plate



The straight pattern hook and band hinges are for hanging the door or gate in front of the frame or post. They are ideal for heavy weight, high use doors, gates, garages and stables in domestic and agricultural applications. Depending on the weight distribution of the gate, the top or bottom pin can be mounted upside down to prevent unwanted removal of the gate.



Technical Data								
Band Length (mm)	250	300	350	400	450	600	750	900
Band Thickness (mm)	4.8	4.8	4.8	4.8	4.8	5.4	5.4	5.4
Band Width (mm)	40	40	40	40	50	50	50	50
Pin Ø (mm)	12	12	12	12	16	16	19	19
Pin Ø (inch)	½	½	½	½	5/8	¾	¾	¾
Hook Plate L (mm)	115	115	115	115	160	160	200	200
Hook Plate W (mm)	40	40	40	40	50	50	75	75
No. of Bolt Holes (Pair)	2	2	2	2	2	2	2	2
Carriage Bolt Ø (mm)	M10	M10	M10	M10	M10	M10	M10	M10
No. of Screw Holes (Pair)	12	12	12	14	14	14	14	16
Screw Ø (mm)	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0

Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

Product Code		Band Length (mm)	Band Length (inch)	To Suit Gate Width (mm)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised					
TIMBAG - FIXINGS INCLUDED						
HBS250B	HBS250G	250	10	500 - 750	1 Pair	5 Pairs
HBS300B	-	300	12	600 - 900	1 Pair	5 Pairs
HBS350B	HBS350G	350	14	700 - 1050	1 Pair	5 Pairs
-	HBS400G	400	16	800 - 1200	1 Pair	5 Pairs
HBS450B	HBS450G	450	18	900 - 1350	1 Pair	5 Pairs
HBS600B	HBS600G	600	24	1200 - 1800	1 Pair	5 Pairs
HBS750B	HBS750G	750	30	1500 - 2250	1 Pair	5 Pairs
HBS900B	HBS900G	900	36	1800 - 2700	1 Pair	5 Pairs

FGH03

Cranked Band & Hook on Plate



The cranked pattern hook and band hinges are for hanging the door or gate flush with the frame or post. They are ideal for heavy weight, high use doors, gates, garages and stables in domestic and agricultural applications. Depending on the weight distribution of the gate, the top or bottom pin can be mounted upside down to prevent unwanted removal of the gate.



Technical Data									
Band Length (mm)	250	300	350	400	450	500	600	750	900
Band Thickness (mm)	4.8	4.8	4.8	4.8	4.8	4.8	5.4	5.4	5.4
Band Width (mm)	40	40	40	40	50	50	50	50	50
Pin Ø (mm)	12	12	12	12	16	16	16	19	19
Pin Ø (inch)	½	½	½	½	¾	¾	¾	¾	¾
Hook Plate L (mm)	115	115	115	115	160	160	160	200	200
Hook Plate W (mm)	40	40	40	40	50	50	50	75	75
No. of Bolt Holes (Pair)	2	2	2	2	2	2	2	2	2
Carriage Bolt Ø (mm)	M10	M10	M10	M10	M10	M10	M10	M10	M10
No. of Screw Holes (Pair)	12	12	12	14	14	14	14	14	16
Screw Ø (mm)	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0


Doors/gates over 7ft height, should be fitted with a third hinge to prevent warping.

Product Code		Band Length (mm)	Band Length (inch)	To Suit Gate Width (mm)	Pack Qty (pcs)	Carton Qty (packs)
Epoxy Black	Hot Dipped Galvanised					
TIMBAG - FIXINGS INCLUDED						
HBC250B	HBC250G	250	10	500 - 750	1 Pair	5 Pairs
HBC350B	HBC350G	350	14	700 - 1050	1 Pair	5 Pairs
HBC450B	HBC450G	450	18	900 - 1350	1 Pair	5 Pairs
HBC500B	HBC500G	500	20	1000 - 1500	1 Pair	5 Pairs
HBC600B	HBC600G	600	24	1200 - 1800	1 Pair	5 Pairs
HBC750B	HBC750G	750	30	1500 - 2250	1 Pair	5 Pairs
HBC900B	HBC900G	900	36	1800 - 2700	1 Pair	5 Pairs

FGH02

Curved Rail Hinge Set

Curved rail hinge sets are ideal for flush mounted fully framed gates with a curved top edge. Depending on the weight distribution of the gate, the top or bottom pin can be mounted upside down to prevent unwanted removal of the gate.



Left Hand

Right Hand

Technical Data					
Top Band Length (mm)					300
Band Width					40
Band Thickness (mm)					4.8
Pin Ø (mm)					12
Pin Ø (inch)					½
Hook Plate L x W (mm)					160 x 50
No. of Bolt Holes (Pair)					2
Carriage Bolt Ø (mm)					M10
No. of Screw Holes (Pair)					13
Screw Ø (mm)					6.0

Product Code		Top Band Length (mm)	Top Band Length (inch)	Bottom Band Length (mm)	Pack Qty (pcs)	Carton Qty (packs)
Hot Dipped Galvanised	Hand					
BAG						
CRHLG	Left	300	12	200	1 Pair	5 Pairs
CRHRG	Right	300	12	200	1 Pair	5 Pairs

HGB05