

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name: Cold Galvanising Paint
Product Code: 237750
UFI: UWE7-SPNS-F00K-7TM6

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Use of the substance/mixture : Spraying paint (spray can)

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

| | | |
|----------|---|--|
| Supplier | T.I Midwood & Co. Ltd TIMCO House Green Lane Wardle Nantwich CW5 6BJ | T.I Midwood & Co. Ltd Aviemore House Hill Street Monahan Ireland |
|----------|---|--|

Emergency Telephone: 01865 407333
(24 hour service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

| | |
|--|-----------|
| Aerosol, Category 1 | H222;H229 |
| Serious eye damage/eye irritation, Category 2 | H319 |
| Specific target organ toxicity – Single exposure, Category 3, Narcosis | H336 |
| Hazardous to the aquatic environment – Chronic Hazard, Category 2 | H411 |

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects




Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

| | | | | |
|--------------------------------|---|---|---|--|
| Hazard pictograms (CLP) | : |  |  |  |
| | | GHS02 | GHS07 | GHS09 |
| Signal word (CLP) | : | Danger | | |
| Contains | : | Acetone | | |
| Hazard statements (CLP) | : | H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects. | | |
| Precautionary statements (CLP) | : | P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours, spray. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, eye protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F. P501 - Dispose of contents/ container in accordance with local regulations. | | |
| EUH-statements | : | EUH066 - Repeated exposure may cause skin dryness or cracking. | | |
| Child-resistant fastening | : | Not applicable | | |
| Tactile warning | : | Not applicable | | |

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|-----------|---|
| Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) substance with national workplace exposure limit(s) (BE, CZ, GB, GR, HR) (Note K) | CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6 | 24.9 – 50 | Flam. Gas 1A, H220 Press. Gas |
| Acetone substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit | CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49 | 24.9 – 50 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 |

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|-----------------|---|
| Zinc powder - zinc dust (stabilised) substance with national workplace exposure limit(s) (SK) | CAS-No.: 7440-66-6 EC-No.: 231-175-3 EC Index-No.: 030-001-01-9 REACH-no: 01-2119467174-37 | 10 – 20 | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| Xylene (mixture of isomers) substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit (Note C) | CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32 | 5 – 10 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 |
| n-butyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, IS, MK, RS, CH); substance with a Community workplace exposure limit | CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29 | 1 – 5 | Flam. Liq. 3, H226 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066 |
| 1-methoxypropan-2-ol substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit | CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35 | 1 – 5 | Flam. Liq. 3, H226 STOT SE 3, H336 |
| Ethylbenzene substance with national workplace exposure limit(s) (AT, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit | CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 | 1 – 5 | Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 |
| Quartz (SiO ₂) substance with national workplace exposure limit(s) (AT, BE, DK, EE, ES, FI, FR, HR, IE, LT, NL, PL, PT, SE, SK, NO, MK, CH); substance with a Community workplace exposure limit | CAS-No.: 14808-60-7 EC-No.: 238-878-4 | 0.0000001 – 0.1 | Not classified |
| Methyl methacrylate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, AL, IS, NO, MK, RS, CH, TR); substance with a Community workplace exposure limit (Note D) | CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6 | 0.0000001 – 0.1 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 |
| Butyl methacrylate substance with national workplace exposure limit(s) (DK, EE, LT, LV, PL, RO, SE, IS, NO) (Note D) | CAS-No.: 97-88-1 EC-No.: 202-615-1 EC Index-No.: 607-033-00-5 REACH-no: 01-2119486394-28 | 0.0000001 – 0.1 | Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 |

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|--------------------|---|
| 2-methoxypropanol substance with national workplace exposure limit(s) (AT, DE, DK, ES, SI, SK, IS, NO, MK, CH) | CAS-No.: 1589-47-5 EC-No.: 216-455-5 EC Index-No.: 603-106-00-0 | 0.0000001 – 0.1 | Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 1B, H360D STOT SE 3, H335 |

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Note K: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : Call a poison center or a doctor if you feel unwell. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Wash skin with plenty of water. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|---|
| Symptoms/effects | : May cause drowsiness or dizziness. |
| Symptoms/effects after inhalation | : Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. |
| Symptoms/effects after skin contact | : None under normal conditions. |
| Symptoms/effects after eye contact | : Eye irritation. |
| Symptoms/effects after ingestion | : None under normal conditions. |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Special hazards arising from the substance or mixture

| | |
|--|---|
| Fire hazard | : Extremely flammable aerosol. |
| Explosion hazard | : Pressurised container: May burst if heated. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. |

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

5.3. Advice for firefighters

- | | |
|--------------------------------|---|
| Firefighting instructions | : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|---|
| General measures | : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage. |
|------------------|---|

6.1.1. For non-emergency personnel

- | | |
|----------------------|---|
| Protective equipment | : Wear recommended personal protective equipment. |
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. |

6.1.2. For emergency responders

- | | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Evacuate unnecessary personnel. Stop leak if safe to do so. |

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|---|
| For containment | : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible. |
| Methods for cleaning up | : Mechanically recover the product. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-----------------------------------|---|
| Additional hazards when processed | : Not expected to present a significant hazard under anticipated conditions of normal use. |
| Precautions for safe handling | : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|---------------------|---|
| Technical measures | : Keep in a cool, well-ventilated place away from heat. |
| Storage conditions | : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. |
| Packaging materials | : Store always product in container of same material as original container. |

7.3. Specific end use(s)

No additional information available

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

| Xylene (mixture of isomers) (1330-20-7) | |
|--|---|
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | Xylene, mixed isomers, pure |
| IOEL TWA | 221 mg/m ³ |
| | 50 ppm |
| IOEL STEL | 442 mg/m ³ |
| | 100 ppm |
| Remark | Skin |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| United Kingdom - Occupational Exposure Limits | |
| Local name | Xylene |
| WEL TWA (OEL TWA) | 220 mg/m ³ o-,m-,p- or mixed isomers |
| | 50 ppm o-,m-,p- or mixed isomers |
| WEL STEL (OEL STEL) | 441 mg/m ³ o-,m-,p- or mixed isomers |
| | 100 ppm o-,m-,p- or mixed isomers |
| Remark | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| United Kingdom - Biological limit values | |
| Local name | Xylene, o-, m-, p- or mixed isomers |
| BMGV | 650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| n-butyl acetate (123-86-4) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | n-Butyl acetate |
| IOEL TWA | 241 mg/m ³ |
| | 50 ppm |
| IOEL STEL | 723 mg/m ³ |
| | 150 ppm |
| Regulatory reference | COMMISSION DIRECTIVE (EU) 2019/1831 |
| United Kingdom - Occupational Exposure Limits | |
| Local name | Butyl acetate |
| WEL TWA (OEL TWA) | 724 mg/m ³ |
| | 150 ppm |
| WEL STEL (OEL STEL) | 966 mg/m ³ |
| | 200 ppm |

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

| | |
|---|---|
| n-butyl acetate (123-86-4) | |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| Acetone (67-64-1) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | Acetone |
| IOEL TWA | 1210 mg/m ³ |
| | 500 ppm |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| United Kingdom - Occupational Exposure Limits | |
| Local name | Acetone |
| WEL TWA (OEL TWA) | 1210 mg/m ³ |
| | 500 ppm |
| WEL STEL (OEL STEL) | 3620 mg/m ³ |
| | 1500 ppm |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| 1-methoxypropan-2-ol (107-98-2) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | 1-Methoxypropanol-2 |
| IOEL TWA | 375 mg/m ³ |
| | 100 ppm |
| IOEL STEL | 568 mg/m ³ |
| | 150 ppm |
| Remark | Skin |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| United Kingdom - Occupational Exposure Limits | |
| Local name | 1-Methoxypropan-2-ol |
| WEL TWA (OEL TWA) | 375 mg/m ³ |
| | 100 ppm |
| WEL STEL (OEL STEL) | 560 mg/m ³ |
| | 150 ppm |
| Remark | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| Ethylbenzene (100-41-4) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | Ethylbenzene |
| IOEL TWA | 442 mg/m ³ |
| | 100 ppm |
| IOEL STEL | 884 mg/m ³ |
| | 200 ppm |

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

| Ethylbenzene (100-41-4) | |
|---|---|
| Remark | Skin |
| Regulatory reference | COMMISSION DIRECTIVE 2000/39/EC |
| United Kingdom - Occupational Exposure Limits | |
| Local name | Ethylbenzene |
| WEL TWA (OEL TWA) | 441 mg/m ³ |
| | 100 ppm |
| WEL STEL (OEL STEL) | 552 mg/m ³ |
| | 125 ppm |
| Remark | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| Quartz (SiO2) (14808-60-7) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | Silica crystalline (Quartz) |
| IOEL TWA | 0.05 mg/m ³ (respirable dust) |
| Remark | (Year of adoption 2003) |
| Regulatory reference | SCOEL Recommendations |
| Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7) | |
| United Kingdom - Occupational Exposure Limits | |
| Local name | Liquefied petroleum gas |
| WEL TWA (OEL TWA) | 1750 mg/m ³ |
| | 1000 ppm |
| WEL STEL (OEL STEL) | 2180 mg/m ³ |
| | 1250 ppm |
| Remark | Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene)) |
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |
| Methyl methacrylate (80-62-6) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | Methyl methacrylate |
| IOEL TWA | 50 ppm |
| IOEL STEL | 100 ppm |
| Regulatory reference | COMMISSION DIRECTIVE 2009/161/EU |
| United Kingdom - Occupational Exposure Limits | |
| Local name | Methyl methacrylate |
| WEL TWA (OEL TWA) | 208 mg/m ³ |
| | 50 ppm |
| WEL STEL (OEL STEL) | 416 mg/m ³ |
| | 100 ppm |

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

| Methyl methacrylate (80-62-6) | |
|-------------------------------|---------------------------------------|
| Regulatory reference | EH40/2005 (Fourth edition, 2020). HSE |

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:
Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses

| Eye protection | | | |
|----------------|----------------------|-----------------|----------|
| Type | Field of application | Characteristics | Standard |
| Safety glasses | | | EN 166 |

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Protective gloves

| Hand protection | | | | | |
|---------------------------------------|----------|------------|----------------|-------------|------------|
| Type | Material | Permeation | Thickness (mm) | Penetration | Standard |
| Disposable gloves, Reusable gloves | | | | | EN ISO 374 |

8.2.2.3. Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | : Liquid |
| Appearance | : Aerosol. |
| Colour | : Silver-grey. |
| Odour | : No data available |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : < -40 °C |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Extremely flammable aerosol. |
| Vapour pressure | : No data available |
| Relative vapour density at 20°C | : No data available |
| Relative density | : No data available |
| Solubility | : No data available |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Viscosity, kinematic | : > 20.5 mm²/s |
| Viscosity, dynamic | : No data available |
| Explosive properties | : Pressurised container: May burst if heated. |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

| | |
|-------------|-----------|
| VOC content | : 614 g/l |
|-------------|-----------|

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Xylene (mixture of isomers) (1330-20-7)

| | |
|--------------------|---|
| LD50 dermal rabbit | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other: |
|--------------------|---|

Acetone (67-64-1)

| | |
|-----------------------|--|
| LD50 oral rat | 5800 mg/kg bodyweight Animal: rat, Animal sex: female |
| LC50 Inhalation - Rat | 76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4 |

1-methoxypropan-2-ol (107-98-2)

| | |
|-----------------|---|
| LD50 dermal rat | > 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)) |
|-----------------|---|

Methyl methacrylate (80-62-6)

| | |
|--------------------|---|
| LD50 dermal rabbit | > 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
|--------------------|---|

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

Xylene (mixture of isomers) (1330-20-7)

| | |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

n-butyl acetate (123-86-4)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

Acetone (67-64-1)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

1-methoxypropan-2-ol (107-98-2)

| | |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |
|----------------------|------------------------------------|

2-methoxypropanol (1589-47-5)

| | |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

Methyl methacrylate (80-62-6)

| | |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

Butyl methacrylate (97-88-1)

| | |
|----------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |
|----------------------|-----------------------------------|

STOT-repeated exposure : Not classified

Xylene (mixture of isomers) (1330-20-7)

| | |
|----------------------------|---|
| LOAEL (oral, rat, 90 days) | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

| | |
|---|---|
| 1-methoxypropan-2-ol (107-98-2) | |
| LOAEL (oral, rat, 90 days) | 2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents) |
| NOAEL (oral, rat, 90 days) | 919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents) |
| NOAEL (dermal, rat/rabbit, 90 days) | > 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |
| Ethylbenzene (100-41-4) | |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
| Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7) | |
| LOAEC (inhalation, rat, gas, 90 days) | 12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other: |
| Butyl methacrylate (97-88-1) | |
| LOAEC (inhalation, rat, gas, 90 days) | 952 ppm Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study) |
| NOAEL (oral, rat, 90 days) | 120 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
| Aspiration hazard : Not classified | |
| COLD GALVANISED PAINT (237750) 380ML | |
| Vaporizer | Aerosol |
| Viscosity, kinematic | > 20.5 mm ² /s |
| 1-methoxypropan-2-ol (107-98-2) | |
| Viscosity, kinematic | 1.848 mm ² /s |
| Ethylbenzene (100-41-4) | |
| Viscosity, kinematic | 0.6 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)' Remarks on result: 'other:' |
| Methyl methacrylate (80-62-6) | |
| Viscosity, kinematic | 0.561 mm ² /s |
| Butyl methacrylate (97-88-1) | |
| Viscosity, kinematic | 1.06 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)' Remarks on result: 'other:' |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|--|
| Ecology - general | : Toxic to aquatic life with long lasting effects. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified |
| Hazardous to the aquatic environment, long-term (chronic) | : Toxic to aquatic life with long lasting effects. |

| | |
|--|--|
| Xylene (mixture of isomers) (1330-20-7) | |
| EC50 - Crustacea [1] | > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia |
| LOEC (chronic) | 3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

| | |
|---|--|
| Xylene (mixture of isomers) (1330-20-7) | |
| NOEC chronic fish | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |
| n-butyl acetate (123-86-4) | |
| EC50 - Other aquatic organisms [1] | 32 mg/l Test organisms (species): Artemia salina |
| EC50 72h - Algae [1] | 674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus) |
| Acetone (67-64-1) | |
| LOEC (chronic) | > 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | ≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| 1-methoxypropan-2-ol (107-98-2) | |
| EC50 - Other aquatic organisms [1] | 2954 mg/l Test organisms (species): other aquatic crustacea: |
| Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7) | |
| LC50 - Fish [1] | 0.362 mg/l |
| EC50 - Crustacea [1] | 0.018 mg/l |
| ErC50 algae | 7.6 mg/l Source: ECOTOX |
| Methyl methacrylate (80-62-6) | |
| LC50 - Fish [1] | > 79 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) |
| EC50 - Crustacea [1] | 69 mg/l Test organisms (species): Daphnia magna |
| EC50 72h - Algae [1] | > 110 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |
| LOEC (chronic) | 68 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC (chronic) | 37 mg/l Test organisms (species): Daphnia magna Duration: '21 d' |
| NOEC chronic fish | 9.4 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d' |
| Butyl methacrylate (97-88-1) | |
| LC50 - Fish [1] | 11 mg/l Test organisms (species): Pimephales promelas |
| LC50 - Fish [2] | 5.57 mg/l Test organisms (species): Oryzias latipes |
| EC50 - Crustacea [1] | 32 mg/l Test organisms (species): Daphnia magna |
| EC50 72h - Algae [1] | 31.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) |

12.2. Persistence and degradability

| | |
|---|------------------------|
| COLD GALVANISED PAINT (237750) 380ML | |
| Persistence and degradability | Not rapidly degradable |
| Xylene (mixture of isomers) (1330-20-7) | |
| Persistence and degradability | Not rapidly degradable |
| Zinc powder - zinc dust (stabilised) (7440-66-6) | |
| Persistence and degradability | Not rapidly degradable |

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

| | |
|---|------------------------|
| n-butyl acetate (123-86-4) | |
| Persistence and degradability | Not rapidly degradable |
| Acetone (67-64-1) | |
| Persistence and degradability | Not rapidly degradable |
| 1-methoxypropan-2-ol (107-98-2) | |
| Persistence and degradability | Not rapidly degradable |
| 2-methoxypropanol (1589-47-5) | |
| Persistence and degradability | Not rapidly degradable |
| Ethylbenzene (100-41-4) | |
| Persistence and degradability | Not rapidly degradable |
| Quartz (SiO₂) (14808-60-7) | |
| Persistence and degradability | Not rapidly degradable |
| Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7) | |
| Persistence and degradability | Not rapidly degradable |
| Methyl methacrylate (80-62-6) | |
| Persistence and degradability | Not rapidly degradable |
| Butyl methacrylate (97-88-1) | |
| Persistence and degradability | Not rapidly degradable |

12.3. Bioaccumulative potential

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)

| | |
|---|----------------------|
| Partition coefficient n-octanol/water (Log Pow) | ≤ 2.8 Source: IUCLID |
|---|----------------------|

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--|---|
| Regional waste regulation | : Disposal must be done according to official regulations. |
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Sewage disposal recommendations | : Disposal must be done according to official regulations. |
| Product/Packaging disposal recommendations | : Disposal must be done according to official regulations. |
| Additional information | : Do not re-use empty containers. |

Cold Galvanising Paint - Safety Data Sheet






According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

HP Code

: HP3 - "Flammable:"
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

| ADR | IMDG | IATA | ADN | RID |
|--|---|---|--|---|
| 14.1. UN number | | | | |
| UN 1950 | UN 1950 | UN 1950 | UN 1950 | UN 1950 |
| 14.2. UN proper shipping name | | | | |
| AEROSOLS | AEROSOLS | Aerosols, flammable | AEROSOLS | AEROSOLS |
| Transport document description | | | | |
| UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS | UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS | UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS | UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS | UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS |
| 14.3. Transport hazard class(es) | | | | |
| 2.1 | 2.1 | 2.1 | 2.1 | 2.1 |
|  |  |  |  |  |
| 14.4. Packing group | | | | |
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment: Yes | Dangerous for the environment: Yes Marine pollutant: Yes | Dangerous for the environment: Yes | Dangerous for the environment: Yes | Dangerous for the environment: Yes |
| No supplementary information available | | | | |

14.6. Special precautions for user

Overland transport

Classification code (ADR)

: 5F

Special provisions (ADR)

: 190, 327, 344, 625

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

| | |
|---|-----------------|
| Limited quantities (ADR) | : 1I |
| Excepted quantities (ADR) | : E0 |
| Packing instructions (ADR) | : P207, LP200 |
| Special packing provisions (ADR) | : PP87, RR6, L2 |
| Mixed packing provisions (ADR) | : MP9 |
| Transport category (ADR) | : 2 |
| Special provisions for carriage - Packages (ADR) | : V14 |
| Special provisions for carriage - Loading, unloading and handling (ADR) | : CV9, CV12 |
| Special provisions for carriage - Operation (ADR) | : S2 |
| Tunnel restriction code (ADR) | : D |

Transport by sea

| | |
|-----------------------------------|------------------------------------|
| Special provisions (IMDG) | : 63, 190, 277, 327, 344, 381, 959 |
| Limited quantities (IMDG) | : SP277 |
| Excepted quantities (IMDG) | : E0 |
| Packing instructions (IMDG) | : P207, LP200 |
| Special packing provisions (IMDG) | : PP87, L2 |
| EmS-No. (Fire) | : F-D |
| EmS-No. (Spillage) | : S-U |
| Stowage category (IMDG) | : None |
| Stowage and handling (IMDG) | : SW1, SW22 |
| Segregation (IMDG) | : SG69 |

Air transport

| | |
|--|--------------------|
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provisions (IATA) | : A145, A167, A802 |
| ERG code (IATA) | : 10L |

Inland waterway transport

| | |
|-----------------------------------|----------------------|
| Classification code (ADN) | : 5F |
| Special provisions (ADN) | : 190, 327, 344, 625 |
| Limited quantities (ADN) | : 1 L |
| Excepted quantities (ADN) | : E0 |
| Equipment required (ADN) | : PP, EX, A |
| Ventilation (ADN) | : VE01, VE04 |
| Number of blue cones/lights (ADN) | : 1 |

Rail transport

| | |
|---|----------------------|
| Classification code (RID) | : 5F |
| Special provisions (RID) | : 190, 327, 344, 625 |
| Limited quantities (RID) | : 1L |
| Excepted quantities (RID) | : E0 |
| Packing instructions (RID) | : P207, LP200 |
| Special packing provisions (RID) | : PP87, RR6, L2 |
| Mixed packing provisions (RID) | : MP9 |
| Transport category (RID) | : 2 |
| Special provisions for carriage – Packages (RID) | : W14 |
| Special provisions for carriage - Loading, unloading and handling (RID) | : CW9, CW12 |
| Colis express (express parcels) (RID) | : CE2 |
| Hazard identification number (RID) | : 23 |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

VOC content : 614 g/l

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

| Name | CAS-No. | Combined Nomenclature code (CN) | Combined Nomenclature code for mixture without constituents which would determine classification under another CN code |
|---------|---------|---------------------------------|--|
| Acetone | 67-64-1 | 2914 11 00 | ex 3824 99 92 |

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

| Name | CN designation | CAS-No. | CN code | Category, Subcategory | Threshold | Annex |
|---------|----------------|---------|------------|-----------------------|-----------|---------|
| Acetone | | 67-64-1 | 2914 11 00 | Category 3 | | Annex I |

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

SECTION 16: Other information

Abbreviations and acronyms:

| | |
|---------|---|
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| BLV | Biological limit value |
| BOD | Biochemical oxygen demand (BOD) |
| COD | Chemical oxygen demand (COD) |
| DMEL | Derived Minimal Effect level |
| DNEL | Derived-No Effect Level |
| EC-No. | European Community number |
| EC50 | Median effective concentration |
| EN | European Standard |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Median lethal concentration |
| LD50 | Median lethal dose |
| LOAEL | Lowest Observed Adverse Effect Level |
| NOAEC | No-Observed Adverse Effect Concentration |
| NOAEL | No-Observed Adverse Effect Level |
| NOEC | No-Observed Effect Concentration |
| OECD | Organisation for Economic Co-operation and Development |
| OEL | Occupational Exposure Limit |
| PBT | Persistent Bioaccumulative Toxic |
| PNEC | Predicted No-Effect Concentration |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| SDS | Safety Data Sheet |
| STP | Sewage treatment plant |
| ThOD | Theoretical oxygen demand (ThOD) |
| TLM | Median Tolerance Limit |
| VOC | Volatile Organic Compounds |
| CAS-No. | Chemical Abstract Service number |
| N.O.S. | Not Otherwise Specified |
| vPvB | Very Persistent and Very Bioaccumulative |
| ED | Endocrine disrupting properties |

Full text of H- and EUH-statements:

| | |
|-----------------------|-------------------------------------|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
|-----------------------|-------------------------------------|

Cold Galvanising Paint - Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

| Full text of H- and EUH-statements: | |
|-------------------------------------|--|
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment – Acute Hazard, Category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment – Chronic Hazard, Category 1 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment – Chronic Hazard, Category 3 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| Eye Dam. 1 | Serious eye damage/eye irritation, Category 1 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Gas 1A | Flammable gases, Category 1A |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| H220 | Extremely flammable gas. |
| H222 | Extremely flammable aerosol. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H229 | Pressurised container: May burst if heated. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H360D | May damage the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| Press. Gas | Gases under pressure |
| Repr. 1B | Reproductive toxicity, Category 1B |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| Skin Sens. 1 | Skin sensitisation, Category 1 |
| STOT RE 2 | Specific target organ toxicity – Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.