

Unreinforced Frames

100 Range

Zinc Yellow



PHILLIPS

- Countersunk head with ribs
- High-Low thread
- Slash tip

Multiple uses for fitting a variety of hardware to frames where there is no steel or aluminium reinforcement present.
*Repair screws for stripped holes.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Zinc					
104Z	4.3 x 25	PH2	1,000	8	384
105Z	4.3 x 30	PH2	1,000	8	384
106Z	4.3 x 40	PH2	1,000	8	192
109Z*	4.8 x 25	PH2	1,000	8	384
Yellow					
104Y	4.3 x 25	PH2	1,000	8	384
105Y	4.3 x 30	PH2	1,000	8	384
106Y	4.3 x 40	PH2	1,000	8	192
109Y*	4.8 x 25	PH2	1,000	8	384

WIN01

200 Range

Zinc Yellow A2/Aust. SS




PHILLIPS

- Countersunk head with ribs
- Single thread
- Gimlet tip

Multiple uses for fitting a variety of hardware to frames where there is no steel or aluminium reinforcement present.
*Repair screws for stripped holes.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Zinc					
201Z	4.3 x 16	PH2	1,000	15	540
202Z	4.3 x 20	PH2	1,000	15	540
203Z	4.3 x 35	PH2	1,000	6	288
204Z	4.3 x 25	PH2	1,000	8	384
205Z	4.3 x 30	PH2	1,000	8	384
206Z	4.3 x 40	PH2	1,000	8	192
207Z	4.3 x 45	PH2	500	8	384
208Z	4.3 x 55	PH2	500	6	288
209Z*	4.8 x 25	PH2	1,000	8	384
210Z*	4.8 x 38	PH2	1,000	8	192

WIN01



Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Yellow					
201Y	4.3 x 16	PH2	1,000	15	540
202Y	4.3 x 20	PH2	1,000	15	540
203Y	4.3 x 35	PH2	1,000	6	288
204Y	4.3 x 25	PH2	1,000	8	384
205Y	4.3 x 30	PH2	1,000	8	384
206Y	4.3 x 40	PH2	1,000	8	192
207Y	4.3 x 45	PH2	500	8	384
208Y	4.3 x 55	PH2	500	6	288
209Y*	4.8 x 25	PH2	1,000	8	384

WIN01

A2/Aust. Stainless Steel					
202SS	4.3 x 20	PH2	1,000	15	540
203SS	4.3 x 35	PH2	1,000	6	288
204SS	4.3 x 25	PH2	1,000	8	384
205SS	4.3 x 30	PH2	1,000	8	384
206SS	4.3 x 40	PH2	1,000	8	192
209SS*	4.8 x 25	PH2	1,000	8	384

WSS01

111 Range

Zinc



PHILLIPS



FRICTION STAY

- Shallow pan countersunk head
- High-Low thread
- Slash tip

For attaching friction stays to PVCu frames. An alternative to the single thread range offering a slash point and a High-Low thread to aid speed of insertion and pull out.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Zinc					
111Z	4.3 x 20	PH2	1,000	8	384
112Z	4.3 x 25	PH2	1,000	8	384

WIN01

215 Range

Zinc A2/Aust. SS



PHILLIPS



FRICTION STAY

- Shallow pan head with serrations
- Single thread
- Gimlet tip

For attaching friction stays with pre-drilled holes to PVCu frames.
Stainless steel screws should be used where there is a corrosive environment.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Zinc					
215Z	4.8 x 16	PH2	1,000	8	384
216Z	4.8 x 20	PH2	1,000	8	384
217Z	4.8 x 25	PH2	1,000	6	288
218Z	4.8 x 30	PH2	1,000	8	192

WIN07

A2/Aust. Stainless Steel					
215SS	4.8 x 16	PH2	1,000	8	384
216SS	4.8 x 20	PH2	1,000	8	384
217SS	4.8 x 25	PH2	1,000	6	288
218SS	4.8 x 30	PH2	1,000	8	192

WSS02

211 Range

Zinc A2/Aust. SS



PHILLIPS



FRICTION STAY

- Shallow pan countersunk head
- Single thread
- Gimlet tip

For attaching friction stays with countersunk holes to PVCu frames.
Stainless steel screws should be used where there is a corrosive environment.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Zinc					
211Z	4.3 x 20	PH2	1,000	8	384
212Z	4.3 x 25	PH2	1,000	8	384
213Z	4.3 x 16	PH2	1,000	15	540

WIN07

A2/Aust. Stainless Steel					
211SS	4.3 x 20	PH2	1,000	8	432
212SS	4.3 x 25	PH2	1,000	8	384
213SS	4.3 x 16	PH2	1,000	15	540

WSS02