## **DECLARATION OF PERFORMANCE**

DoP ref. no: NP1306001



| Name of manufacturer | Teco Building Products  |  |
|----------------------|---|--|
|                      | Wellington Road, Portslade, Brighton, BN41 1DN                              |  |
| Product type         | Teco Nailing Plate  |  |
| Intended use         | Structural connection of butt jointed timber members of the same thickness. |  |
| System of AVCP       | 2+  |  |
| Harmonised standard  | EN 14545:2008   |  |

Teco is an ISO9001 registered firm audited by QMS International plc.

Structural Consultants C4Ci Ltd.

Factory Production Control assessed and audited by BM TRADA CE Scheme for Construction Products Notified Body No.1224

Certificate Number: 1224-CPR-0335

Where appropriate, tested by CERAM Research Ltd Notification Body No.1289

Material: Grade DX51D Mild Steel to EN 10346

| Product Code | Width (w) | Length (I) | Thickness (tp) |
|--------------|-----------|------------|----------------|
| NP103X152    | 104mm     | 154mm      | 1mm            |
| NP170X175    | 169mm     | 178mm      | 1mm            |
| NP170X350    | 178mm     | 338mm      | 1mm            |
| NP41X152     | 42mm      | 154mm      | 1mm            |
| NP42X175     | 42mm      | 178mm      | 1mm            |
| NP85X87      | 85mm      | 89mm       | 1mm            |
| NPSTD        | 85mm      | 178mm      | 1mm            |



| <b>Declared Performance</b> |   |                         |
|-----------------------------|---|-------------------------|
| Essential characteristics   | Performance   | Harmonised              |
|                             |   | technical specification |
| Mechanical strength         | Characteristic yield strength of parent plate material: 280 N/mm <sup>2</sup> |                         |
| Mechanical stiffness        | Min. percentage elongation after fracture of parent plate material: 22%       | EN 14545:2008           |
| Durability                  | Z275 Hot dip zinc coating (Service Class 2 acc. to EN1995-1-1)                |                         |

The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Rhonda Backwell Director PLP ackwell

01/07/2013 Brighton