

Technical Data Sheet

Ref: TDS-01-COL-03


Collated Self Drilling Bugle head - PH - Zinc

Features

- Used to secure plasterboard to wall/ceiling track systems with a max of 2mm thickness.
- Self-tapping thread.
- Self-drilling tip.
- Zinc.
- Phillips No. 2 for a positive drive.
- Bugle head to reduce the likelihood of damaging the board surface.
- Conforms to BS EN 14566:2008+A1:2009.
- Unique yellow collated strips are specifically designed to be compatible with all leading power tool brands.
- Conforms to BS EN 10666



Dimensional Data



Product Code	Diameter (D)	Length (L)	Head Diameter (HD)	Drill Point Diameter Ø (DPD)	Drill Point Length (DPL)	Effective Thread Length (ETL)
00035COLLSD	3.5	35	8.25	2.8	3.6	28.5
00042COLLSD	3.5	42	8.25	2.8	3.6	35.5
00045COLLSD	3.5	45	8.25	2.8	3.6	38.5
00050COLLSD	3.5	50	8.25	2.8	3.6	43.5

All stated figures (mm) are approx and for reference only.

Performance Data

Test material	:	S275JR steel test plate
Screw diameter	:	3.5
Test plate thickness	:	2.0
Rec. Pull out (kN)	:	1.49

Test data stated is for reference only as this may not represent the actual figures you may achieve in application.

Installation Data

Diameter	:	4.8
RPM	:	1800-2500
Max. Drill capacity	:	2.0mm

Additional Information

To ensure an effective fixing, thread must be visible behind the supporting steel after application.