

C2 EXTERIOR STRONG-FIX PREMIUM SCREW

DESIGNED FOR
OUTDOOR APPLICATIONS

Ideal for: Ironmongery | Decking | Fencing



**EXTREME
PULL-OUT
RESISTANCE**



**DESIGNED
FOR SUPERIOR
HOLD**



**PRECISION
PZ DRIVE
PREVENTS
"CAM-OUT"**

Exterior

NEW



PZI EN 14592:2008

NOTE: Partially threaded from 80mm. Twin cut tip on 3.5 gauge from 20mm. Helix from 100mm and above.

The silver organic coated C2 Exterior Strong-Fix provides exceptional corrosion resistance for use in harsh environments.

C2 is a revolutionary high-performance screw designed using modern manufacturing methods and an innovative twin-cut point, ensuring consistent and rapid pick-up while reducing timber splitting. Its superior holding strength in a wide variety of materials provides ultimate performance.

- Ribs under head for improved countersinking
- Special plating to give 1,000 hours salt spray resistance
- Multi-layer coating consisting of organic top coat barrier and a zinc base layer
- Dual angle thread for ultimate performance and exceptionally high pull-out resistance
- Patented twin cut technology for rapid "pick-up" and reduces timber splitting



CC205

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
35025C2SBX	3.5 x 25	PZ2	200	75	2700
35030C2SBX	3.5 x 30	PZ2	200	75	1800
40025C2SBX	4.0 x 25	PZ2	200	75	1800
40030C2SBX	4.0 x 30	PZ2	200	75	1800
40040C2SBX	4.0 x 40	PZ2	200	50	1200
40050C2SBX	4.0 x 50	PZ2	200	35	840
40060C2SBX	4.0 x 60	PZ2	200	15	540
40070C2SBX	4.0 x 70	PZ2	200	15	540
45040C2SBX	4.5 x 40	PZ2	200	35	840
45050C2SBX	4.5 x 50	PZ2	200	15	540
45080C2SBX	4.5 x 80	PZ2	200	16	384
50040C2SBX	5.0 x 40	PZ2	200	35	840
50050C2SBX	5.0 x 50	PZ2	200	15	540
50060C2SBX	5.0 x 60	PZ2	200	16	384
50070C2SBX	5.0 x 70	PZ2	200	16	384
50080C2SBX	5.0 x 80	PZ2	200	16	384
50090C2SBX	5.0 x 90	PZ2	100	15	540
50100C2SBX	5.0 x 100	PZ2	100	15	540
60040C2SBX	6.0 x 40	PZ3	200	15	540
60050C2SBX	6.0 x 50	PZ3	200	16	384
60070C2SBX	6.0 x 70	PZ3	200	12	288
60100C2SBX	6.0 x 100	PZ3	100	15	540
60130C2SBX	6.0 x 130	PZ3	100	16	384
60150C2SBX	6.0 x 150	PZ3	100	12	324
TUB (C2 IMPACT POWER BIT INCLUDED)					
60040C2S	6.0 x 40	PZ3	150	12	360
60100C2S	6.0 x 100	PZ3	60	12	360
GRAB PACK (600 PCS)					
C2SGPACK	-	-	600	5	150
4.0 x 30	PZ2	140			
4.0 x 40	PZ2	100			
4.0 x 50	PZ2	70			
4.0 x 60	PZ2	60			
5.0 x 40	PZ2	80			
5.0 x 50	PZ2	55			
5.0 x 60	PZ2	45			
5.0 x 70	PZ2	30			
5.0 x 80	PZ2	20			
Impact 38mm Driver Bits	PZ2	3			



C2 DECK-FIX PREMIUM SCREW

DESIGNED FOR DECKING
PLATFORMS & EXTERNAL
TIMBER CONSTRUCTION



**DESIGNED
FOR SUPERIOR
CLAMPING WITH
HELIX TO STOP
TIMBER JACKING**



**REDUCED
IMPACT
RESISTANT
HEAD FOR A
CLEAN FINISH**



**PRECISION TX
DRIVE PREVENTS
"CAM-OUT"**

Exterior



TX DRIVE EN 14592:2008

The C2 Deck-Fix with a green organic coating ideal for outdoor projects. C2 is a revolutionary high-performance screw designed using modern manufacturing methods and an innovative twin-cut point, ensuring consistent and rapid pick-up while reducing timber splitting. Its superior holding strength in a variety of timber providing an ultimate performance.

- Strengthened head to prevent shearing when installed with an impact tool
- Ribs under the head for improved countersinking
- Helix shank for removing debris and to improve clamping
- Coated with a patented multi-layer corrosion resistant plating to withstand 1,000 hours salt spray
- Patented twin cut technology for rapid "pick-up" and reduces timber splitting

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
50C2D250BX	4.5 x 50	TX20	250	15	540
65C2D250BX	4.5 x 65	TX20	250	18	432
75C2D250BX	4.5 x 75	TX20	250	18	432
85C2D250BX	4.5 x 85	TX20	250	18	432
TUB (DRIVER BIT INCLUDED)					
50C2D250	4.5 x 50	TX20	250	8	288
65C2D250	4.5 x 65	TX20	250	8	288
65C2D1000	4.5 x 65	TX20	1,000	1	72
75C2D250	4.5 x 75	TX20	250	8	216
TIMBAG					
75C2DB	4.5 x 75	TX20	120	5	500
INDUSTRY PACK (1,000 PCS)					
65C2DIND	4.5 x 65	TX20	1,000	3	81

