

Cramps & Ties



Safety Frame Cramp

Traditionally used for securing timber windows and door frames into masonry. They can also be used for restraining masonry to new and existing structures in non structural applications. Two 6mm holes and one 9mm hole.



UK
CA

Product Code	Width (mm)	Projection (mm)	Upstand (mm)	Pack Qty (pcs)	Qty Break (packs)
BOX					
Stainless Steel - 2.0mm					
100SFC	19	100	50	250	10
150SFC	19	150	50	250	10
200SFC	19	200	50	250	10

BMW10

Heavy Duty Fishtailed Cramp

Two 6mm holes and one 8mm hole. Manufactured from galvanised steel for superior corrosion resistance.



Product Code	Width (mm)	Projection (mm)	Upstand (mm)	MOQ Qty (pcs)	Qty Break (packs)
BAG					
Galvanised Steel - 2.3mm					
100FFC	25	100	50	25	100
150FFC	25	150	50	25	100
200FFC	25	200	50	25	100

BMW10

Window Board Tie

A simple solution to tie window boards to masonry.



Product Code	Width (mm)	Projection (mm)	Upstand (mm)	Pack Qty (pcs)	MOQ Qty (pcs)	Qty Break (packs)
BOX						
Galvanised Steel - 2.0mm						
WBT10	12	147	25	10	-	50
WBT	12	147	25	1	100	-

BMW10

Movement Ties

When used with debonding sleeves, provide restraint in one direction and horizontal movement for expansion and contraction found in long spans of brickwork. The tie sits inside the debonding sleeve allowing the tie to move in situ.



UK
CA

Product Code	Width (mm)	Length (mm)	Pack Qty (pcs)
BAG			
Stainless Steel			
TTSSPE150	19	150	250
TTSSPE200	19	200	250

BMW10

Movement Tie Debonding Sleeves

Designed for use with movement ties to provide restraint in one direction and horizontal movement for expansion and contraction found in long spans of brickwork. The debonding sleeve is located over the tie to allow the tie to move.



Product Code	Width (mm)	Length (mm)	Pack Qty (pcs)
BAG			
TTDS120	20	120	250

BMW10

Timber Frame Tie

Timber Frame Ties are suitable for tying masonry outer cladding to softwood structural framework of domestic dwellings and industrial/commercial buildings up to 4 storeys and not greater than 15m in height.

- Complies with a DD140 Type 6 tie.
- Meets with the appropriate parts of NHBC standards.
- Supplied with annular rings hank nails.

UK
CA



Product Code	Width (mm)	Projection (mm)	Cavity Width (mm)	Pack Qty (pcs)	Qty Break (packs)
BOX					
Stainless Steel					
269413	19	130	50	250	10
269846	19	155	75	250	10
269719	19	180	100	250	10

BMW10

Screw-in Frame Tie

Universal frame and wall ties for connecting wooden window and door frames to masonry with the use of a nylon plug.



Product Code	Length (mm)	Thread Length (mm)	Thread Dia (mm)	Pack Qty (pcs)	Qty Break (packs)
BOX					
Zinc & Yellow					
150SFT	150	40	6	100	4

BMW10