

Declaration of Performance

No. DOP-02-CAB-02-T2008 / Page 1 of 2

Carriage Bolts (Class 4.8)



Material - Carbon Steel

Head Type - Domed top, square under the head

Bolt Diameter (mm) - M10

We hereby declare these designated products have performed initial type testing under system 3, Annex V of the regulation (EU) no. 305/2011 (Construction Products Regulation), with the reference to the harmonised European standard (hEN) BS EN 14592:2008+A1:2012 (Timber structures - Dowel type fasteners - Requirements) for screws intended for the use in "load bearing timber structures" and produced the calculation/test reports as attached;

The initial type testing has been carried out by independent notified body;
Strojirensky Zkusebni Ustav, NB # 1015, Hudcova 424/56B, 621 00 Brno-Medlánky, Czechia

Certificate Number: E-30-20563-13

Test Report Number: No. 30-9958/3


Factory Process Control (FPC) has been established by the factory.

This declaration is valid until there is a significant change in the product and declared characteristics. ie. raw material or change in production process.

This declaration is the responsibility of the importer ; T.I.Midwood & Co. Ltd.

Simon Midwood

Managing Director



TIMCO House
2017

2014/2017

Name

Position

Signature

Location & Date

Test Year

Declaration of Performance

No. DOP-02-CAB-02-T2008 / Page 2 of 2

Carriage Bolts (Class 4.8)

Domed top, square under the head - M10

Material & Geometry

| | |
|----------------------------|--------------|
| Material | Carbon Steel |
| Bolt diameter (mm) | M10 |
| Head diameter (mm) | 24.0 |
| Inner thread diameter (mm) | 9.80 |

Mechanical Strength & Stiffness

| | |
|--|-------|
| Characteristic yield moment $M_{y,k}$ at 9° [Nmm] (thread section) in acc. to EN 409 | 35214 |
| Characteristic tensile strength R_m [MPa] in acc. with EN ISO 898-1 | 468 |

Durability

| | |
|----------------------|-------------------------------------|
| Coating (Finish) | Green Organic |
| Corrosion protection | Service Class 3 acc. to EN 1995-1-1 |