

Welded Link Chains



Welded link chain is ideal for securing farm gates and machinery among a variety of other uses. Not suitable for overhead lifting, load binding or towing.



Product Code	Length (m)	Shackle Ø (mm)	Inner Link L (mm)	Inner Link W (mm)	Safe Working Load (kg)	Pack Qty (pcs)	Carton Qty (packs)
Hot Dipped Galvanised							
EACH							
432HDGC	3.0	4	32	8	80	1	20
642HDGC	2.0	6	42	12	160	1	15
852HDGC	1.5	8	52	16	320	1	10
432HDGC10	10.0	4	32	8	80	1	6
521HDGC10	10.0	5	21	10	125	1	4
642HDGC10	10.0	6	42	12	160	1	3
Zinc							
BOX							
326BZPC10	10.0	3	26	8	40	1	8

L=LENGTH W=WIDTH

GAP08

Single Link Jack Chain

Ideal for the hanging of light fittings, pictures, mirrors, signs and hanging flower baskets. Zinc plated for improved resistance to corrosion.



Product Code	Length (m)	Shackle Ø (mm)	Safe Working Load (kg)	Pack Qty (pcs)	Carton Qty (packs)
Zinc					
BOX					
427487	10	3	7.5	1	12

GAP08

Wire Ropes

Wire rope with 7x7 construction and zinc plating for corrosion resistance. Good degree of flexibility and ideal for stay wires, fencing, hanging signs, garage doors and catenary wire.



Product Code	Length (m)	Shackle Ø (mm)	Pack Qty (pcs)	Carton Qty (packs)
Zinc				
BAG				
427506	30	2	1	20
427333	20	3	1	25
427004	10	4	1	20

GAP11

Wire Rope Grips



Wire rope grips used for the formation of an eye or loop at the end of a wire rope. Zinc plated for improved resistance to corrosion.

Product Code	To Suit Rope Size (mm)	Pack Qty (pcs)	Carton Qty (packs)
Zinc			
BAG			
427819	3	20	50

GAP11

Wire Rope Thimbles



Wire rope thimbles are used to protect the eyes of cable and rope slings from abrasion by providing a solid steel barrier between the cable strands and other rigging fittings used in the connection. Zinc plated for improved resistance to corrosion.

Product Code	To Suit Rope Size (mm)	Pack Qty (pcs)	Carton Qty (packs)
Zinc			
BAG			
427110	4	20	50

GAP11