

## Wing-Tip Self-Drilling Screw - For Timber to Light Section Steel

Bi-Metal (SO)

Exterior (SO)

Zinc



PHILLIPS

Specifically designed to attach wood to metal. Coarse self-tapping thread with wings designed to ream out the timber, so the screw can achieve Max R.P.M. without burning out. When the wings hit the metal they will break off to permit the thread to self tap into the metal.

Product Code	Size (mm)	Driver Bit Size	Max. Drilling Thickness (mm)	Effective Thread Length (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
<b>Bi-Metal (Silver Organic)</b>							
<b>BOX</b>							
BMLW38	4.8x 38	PH2	4.0	18	200	16	840
BMLW65	5.5x 65	PH3	5.0	41	200	12	288
BMLW85	5.5x 85	PH3	5.0	47 *P/T	100	16	384
BMR02							
<b>Exterior (Silver Organic)</b>							
<b>BOX (DRIVER BIT INCLUDED)</b>							
LW4238S	4.2x 38	PH2	3.0	19	200	16	768
LW38S	4.8x 38	PH2	4.0	16	200	16	768
LW50S	5.5x 50	PH3	5.0	26	200	16	384
LW65S	5.5x 65	PH3	5.0	41	200	12	288
LW85S	5.5x 85	PH3	5.0	61	100	16	384
LW100S	5.5x 100	PH3	5.0	61 *P/T	100	16	384
RF03							
<b>Zinc</b>							
<b>BOX (DRIVER BIT INCLUDED)</b>							
LW32B	4.2x 32	PH2	4.0	10	200	22	1056
LW4238B	4.2x 38	PH2	3.0	19	200	16	768
LW38B	4.8x 38	PH2	4.0	16	200	16	768
LW50B	5.5x 50	PH3	5.0	26	200	16	384
LW65B	5.5x 65	PH3	5.0	41	200	12	288
LW85B	5.5x 85	PH3	5.0	61	100	16	384
LW100B	5.5x 100	PH3	5.0	61 *P/T	100	16	384
LW130B	5.5x 130	PH3	5.0	61 *P/T	100	8	384
LW150B	5.5x 150	PH3	5.0	61 *P/T	100	12	288
RF04							
<b>TIMBAG</b>							
LW38BB	4.8x 38	PH2	4.0	16	260	5	600
LW50BB	5.5x 50	PH3	5.0	26	150	5	600
LW65BB	5.5x 65	PH3	5.0	41	120	5	600
BAG 12							

\*P/T = PARTIALLY THREADED

BAG 12

## Wing-Tip Self-Drilling Screw - For Timber to Heavy Section Steel

Bi-Metal (SO)

Zinc



PHILLIPS

Specifically designed to attach wood to metal (Max 12mm). Metric thread with wings designed to ream out the timber, so the screw can achieve Max R.P.M. without burning out. When the wings hit the metal they will break off to permit the thread to self tap into the metal.

Product Code	Size (mm)	Driver Bit Size	Max. Drilling Thickness (mm)	Effective Thread Length (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
<b>Bi-Metal (Silver Organic)</b>							
<b>BOX</b>							
BMHW55	5.5x 55	PH3	12.0	24	200	16	384
BMHW65	5.5x 65	PH3	12.0	34	200	12	288
BMHW85	5.5x 85	PH3	12.0	45 *P/T	100	16	384
BMHW120	5.5x 120	PH3	12.0	45 *P/T	100	8	384
BMR02							
<b>Zinc</b>							
<b>BOX (DRIVER BIT INCLUDED)</b>							
HW45B	5.5x 45	PH3	12.0	15	200	15	540
HW65B	5.5x 65	PH3	12.0	31	200	12	288
HW85B	5.5x 85	PH3	12.0	51	100	16	384
HW100B	5.5x 100	PH3	12.0	63	100	16	384
HW120B	5.5x 120	PH3	12.0	51 *P/T	100	8	384
RF04							

\*P/T = PARTIALLY THREADED

RF04