

WD-40[®] SPECIALIST[®] SPRAY GREASE

DATA
SHEET



PRODUCT OVERVIEW

WD-40[®] Specialist[®] Spray Grease is a premium quality spray grease designed for use in areas where long-term lubrication and corrosion protection is required. It is particularly suitable for use on vertical surfaces, where its viscous nature prevents running and displacement. The back-bone of the formula is WD-40[®] itself, ensuring an excellent performance profile.



NARROW SPRAY



WIDE SPRAY

FEATURES & BENEFITS

- Non-drip formula - stays where it's applied, doesn't run
- Very long lasting and economical, contains WD-40[®] MUP Precise application thanks to Smart Straw
- Excellent lubrication and water-displacement properties
- Excellent corrosion protection and adhesion and sealing properties
- High degree of water resistance
- Excellent load carry capacity and good oxidation resistance
- Wide temperature range of -20°C to +115°C as grease, then to +260°C as liquid

RECOMMENDED FOR:

Virtually limitless application areas throughout the home, trade and industry. Any metallic surfaces requiring lubrication and corrosion protection. This product will also protect against seizure caused by corrosion and chemical attack.

DIRECTIONS FOR USE

Spray sparingly onto the component, ensuring an even coating.

TECHNICAL DATA

Appearance	Amber aerosol grease
Odour	WD-40 aroma
4 Ball Wear Test	0.5 mm (ASTM D-4172)
Dropping Point Temp	118°C (ASTM D566)
Corrosion Protection	0 % rust at 72h (ASTM B-117)
Flammability	Classed as extremely flammable
Temperature (Continuous)	-20°C to +115°C as grease, then to +260°C as liquid

