

Cavity Fixings



Spring Toggles

Zinc





A cavity fixing that is ideal for overhead installations.

The wings spread the load over a wider area making them more suited for heavier loads.

11 - 26KG

Technical Data

Substrate	Plasterboard 12.5mm Thickness		
Screw Ø (mm)	M3	M5	M6
Drill Hole Ø (mm)	11	14	18
Min. Cavity Depth (mm)	20	30	30
Rec. Tensile Load (kN)	0.11	0.22	0.26
Max Rec. Load (kg)	11	22	26



Product Code	Screw Ø x L (mm)	Wall & Fixture Thickness (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
T0G350	M3 x 50	30	100	12	240
T0G550	M5 x 50	20	100	12	192
T0G575	M5 x 75	45	100	12	192
T0G5100	M5 x 100	70	100	6	96
T0G675	M6 x 75	45	100	6	96
ANC02					
TIMBAG					
T0G550B	M5 x 50	20	55	5	600
T0G575B	M5 x 75	45	50	5	600
BAG23					
TIMPAC					
T0G550P	M5 x 50	20	4	5	-
T0G575P	M5 x 75	45	4	5	-
PAK34					

Metal Cavity Anchors

Zinc



COMBI





A cavity fixing that is ideal for hanging radiators, brackets, hand rails and shelving units.

When installing multiple anchors a setting tool is recommended.

22 - 37KG

Technical Data

Substrate	Plasterboard 12.5mm Thickness		
Screw Ø (mm)	M4	M5	M6
Drill Hole Ø (mm)	8.0	10.0	12.0
Fixture Hole Ø (mm)	4.0	5.0	6.0
Rec. Tensile Load (kN)	0.22	0.22	0.37
Max Rec. Load (kg)	22	22	37



Product Code	Screw Ø x L (mm)	Anchor Length (mm)	Grip Board (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX						
40038CA	M4 x 45	38	8-16	100	20	640
40045CA	M4 x 50	45	16-23	100	20	640
50037CA	M5 x 45	37	6-13	100	20	480
50052CA	M5 x 60	52	7-16	100	10	320
50065CA	M5 x 70	65	17-32	100	10	320
60052CA	M6 x 60	52	7-16	100	10	320
60065CA	M6 x 70	65	17-32	100	10	280
ANC01						
TIMBAG						
50037CAB	M5 x 45	37	6-13	70	5	600
50052CAB	M5 x 60	52	7-16	60	5	600
60065CAB	M6 x 70	65	17-32	40	5	600
BAG22						
TIMPAC						
50037CAP	M5 x 45	37	6-13	4	5	-
50052CAP	M5 x 60	52	7-16	3	5	-
PAK33						

Setting Tool



A handy and efficient tool used to set cavity anchors.

Product Code	Pack Qty (pcs)	Carton Qty (packs)
BOX		
SET001	1	30
ANC01		

Metal Speed Plugs

Zinc



COMBI



A rapid light duty plasterboard fixing for use in a wide range of


applications. Cross-recess head allows simple installation with a screw driver.

Note: Only metal speed plugs come with screws

5 - 14KG

Technical Data

Substrate	Plasterboard 12.5mm Thickness	
Type	Metal	Nylon
Max. Fixture Thickness (mm)	6.0	
Rec. Tensile Load (kN)	0.14	0.05
Max Rec. Load (kg)	14	5



Product Code	Plug Length (mm)	Screw Ø x L (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
TBAZS	31.5	4.5 x 30	100	15	540
ANP01					
TUB					
TBAZST	31.5	4.5 x 30	300	20	-
ANP01					
TIMBAG					
TBAZSB	31.5	4.5 x 30	75	5	870
BAG24					
TIMPAC					
TBAZSP	31.5	4.5 x 30	5	5	-
PAK35					

Nylon Speed Plugs



Nylon speed plugs are ideal for electrical installation due to non-conductivity of nylon material.

Note: A 6mm pre-drilled hole may be required in harder plasterboards.

Product Code	Plug Length (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX				
TBAN	42	100	10	30,000
ANP02				