



According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830 $\,$

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name: Copper Anti-Seize

Product Code: 237456

UFI: MNM6-YPR2-E003-RF97

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Industrial use, Professional use, Consumer use

Use of the substance/mixture : Grease

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier: T.I Midwood & Co. Ltd T.I Midwood & Co. Ltd

TIMCO House Aviemore House
Green Lane Hill Street
Wardle Monahan
Nantwich Ireland
CW5 6BJ

Emergency Help Line: 01865 407333 (24 hour service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GB CLP (SI 2019:720 as amended)

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Causes skin irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GB CLP)



GHS02





GHS07

GHS09

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Signal word (GB CLP) : Danger

Hazard statements (GB CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (GB CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours, spray.

P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, eye protection. P302+P352 - IF ON SKIN: Wash with plenty of water.

P332+P313 - If skin irritation occurs: Get medical advice, attention.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122

°F.

P501 - Dispose of contents/ container in accordance with local regulations.

Child-resistant fastening : Not applicable Tactile warning : Not applicable

2.3. Other hazards

Component	
Substance(s) not meeting the PBT criteria of UK REACH regulation, in accordance with Annex XIII	Talc (14807-96-6), Diphenylamine (122-39-4), Copper (7440-50-8), n-hexane (110-54-3), Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)
Substance(s) not meeting the vPvB criteria of UK REACH regulation, in accordance with Annex XIII	Talc (14807-96-6), Diphenylamine (122-39-4), Copper (7440-50-8), n-hexane (110-54-3), Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)
Component	
Substance(s) not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP	Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)(68476-85-7), Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Talc(14807-96-6), Copper(7440-50-8), Diphenylamine(122-39-4), n-hexane(110-54-3)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier		Labelling according to GB CLP (SI 2019:720 as amended)
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 UK Index-No.: 649-202-00-6	≥ 50	Flam. Gas 1A, H220 Press. Gas

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Name	Product identifier	%	Labelling according to GB CLP (SI 2019:720 as amended)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC-No.: 921-024-6	10 – 20	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Talc	CAS-No.: 14807-96-6 EC-No.: 238-877-9	10 – 20	Not classified
Copper	CAS-No.: 7440-50-8 EC-No.: 231-159-6 UK Index-No.: 029-024-00-X	2.5 – 3.5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Diphenylamine	CAS-No.: 122-39-4 EC-No.: 204-539-4 UK Index-No.: 612-026-00-5	0.25 – 0.5	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 (ATE=0.5 mg/l/4h) STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
n-hexane	CAS-No.: 110-54-3 EC-No.: 203-777-6 UK Index-No.: 601-037-00-0	0.25 – 0.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
	CAS-No.: 110-54-3 EC-No.: 203-777-6 UK Index-No.: 601-037-00-0	(5 ≤ C ≤ 100) STOT RE 2; H373

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get

medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after eye contact : None under normal conditions. Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry

into sewers or streams. Stop leak without risks if possible.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

Precautions for safe handling

- : Not expected to present a significant hazard under anticipated conditions of normal use.
- Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and

eyes. Wear personal protective equipment.

Hygiene measures

: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this

product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Keep in a cool, well-ventilated place away from heat.

Storage conditions
Packaging materials

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

: Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Talc (14807-96-6)		
United Kingdom - Occupational Exposure Limits		
Local name	Talc	
WEL TWA (OEL TWA)	1 mg/m³ respirable dust	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Diphenylamine (122-39-4)		
United Kingdom - Occupational Exposure Limits		
Local name	Diphenylamine	
WEL TWA (OEL TWA)	10 mg/m³	
WEL STEL (OEL STEL)	20 mg/m³	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Copper (7440-50-8)		
United Kingdom - Occupational Exposure Limits		
Local name	Copper	
WEL TWA (OEL TWA)	0.2 mg/m³ fume (as Cu) 1 mg/m³ and compounds, dusts and mists (as Cu)	
WEL STEL (OEL STEL)	2 mg/m³ and compounds, dusts and mists (as Cu)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
n-hexane (110-54-3)		
United Kingdom - Occupational Exposure Limits		
Local name	n-Hexane	
WEL TWA (OEL TWA)	72 mg/m³	

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

n-hexane (110-54-3)		
	20 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Petroleum gases, liquefied (Contains < 0.1% 1	,3-butadiene) (68476-85-7)	
United Kingdom - Occupational Exposure Limits		
Local name	Liquefied petroleum gas	
WEL TWA (OEL TWA)	1750 mg/m³	
	1000 ppm	
WEL STEL (OEL STEL)	2180 mg/m³	
	1250 ppm	
Remark	Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety glasses			EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Skin and body protection	
Туре	Standard
protective clothing	EN ISO 6530

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves,					EN ISO 374
Reusable gloves					

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : Aerosol. Colour : brown. Odour : Not available Odour threshold : Not available : Not available рΗ Melting point : Not applicable Freezing point : Not available **Boiling point** : -40 - -2 °C (LPG) Flash point : < -40 °C Lower explosion limit : 1.4 vol % (LPG) : 10.9 vol % (LPG) Upper explosion limit : 590 - 1760 kPa (LPG) Vapour pressure

Vapour pressure at 50°C : Not available Relative vapour density at 20°C : Not available Relative density : Not available Density : Not available : Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature : 365 °C (LPG) Decomposition temperature : Not available Viscosity, kinematic : > 20.5 mm²/s

Explosive properties : Pressurised container: May burst if heated.

9.2. Other information

VOC content : 460 g/l
Volatility : Volatile
Particle characteristics : Not applicable

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

,	
Talc (14807-96-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Copper (7440-50-8)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: other:
LC50 Inhalation - Rat	> 5.11 mg/l air Animal: rat, Guideline: OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method), Remarks on results: other:
n-hexane (110-54-3)	
LD50 oral rat	24 ml/kg Source: ECHA
LD50 oral	> 16000 mg/kg bodyweight
LD50 dermal rabbit	> 3350 mg/kg Source: ECHA
LD50 dermal	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 17600 mg/l
LC50 Inhalation - Rat (Vapours)	259.354 mg/l Source: ECHA

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830 $\,$

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat, Remarks on results: other:	
LC50 Inhalation - Rat	> 25.2 mg/l air Animal: rat	
Skin corrosion/irritation : Serious eye damage/irritation : Respiratory or skin sensitisation : Germ cell mutagenicity : Carcinogenicity : Reproductive toxicity : STOT-single exposure : n-hexane (110-54-3) STOT-single exposure	Causes skin irritation. Not classified Not classified Not classified Not classified Not classified Not classified Mot classified Not classified	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes		
STOT-single exposure	May cause drowsiness or dizziness.	
·	Not classified	
Talc (14807-96-6)		
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)	
Diphenylamine (122-39-4)		
NOAEL (oral, rat, 90 days)	3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
n-hexane (110-54-3)		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Petroleum gases, liquefied (Contains < 0.1%	1,3-butadiene) (68476-85-7)	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:	
Aspiration hazard :	Not classified	
COPPER ANTI SEIZE (237456) 380ML		
Vaporizer	Aerosol	
Viscosity, kinematic	> 20.5 mm²/s	
Not able to form a pool	Yes	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes	, cyclics, <5% n-hexane	
Viscosity, kinematic	0.7 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'	
11.2 Information on other hazards		

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Hazardous to the aquatic environment, short-term : Not classified

Hazardous to the aquatic environment, long-term

: Toxic to aquatic life with long lasting effects.

(chronic)

Talc (14807-96-6)		
LC50 - Fish [1]	89581.02 mg/l Test organisms (species): other:	
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:	
EC50 96h - Algae [1]	7202.7 mg/l Test organisms (species): other:	
NOEC (chronic)	1459798 mg/l Test organisms (species): other: Duration: '30 d'	
Diphenylamine (122-39-4)		
EC50 - Crustacea [1]	2 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	2.17 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
n-hexane (110-54-3)		
LC50 - Fish [1]	2.5 mg/l	
EC50 - Crustacea [1]	3.88 mg/l	
EC50 - Other aquatic organisms [1]	50 mg/l waterflea	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)		
LC50 - Fish [1]	0.362 mg/l	
EC50 - Crustacea [1]	0.018 mg/l	
ErC50 algae	7.6 mg/l Source: ECOTOX	

12.2. Persistence and degradability

COPPER ANTI SEIZE (237456) 380ML		
Persistence and degradability	Not rapidly degradable	
Talc (14807-96-6)		
Persistence and degradability	Not rapidly degradable	
Diphenylamine (122-39-4)		
Persistence and degradability Not rapidly degradable		
Copper (7440-50-8)		
Persistence and degradability	Not rapidly degradable	
n-hexane (110-54-3)		
Persistence and degradability Not rapidly degradable		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Persistence and degradability Not rapidly degradable		
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)		
Persistence and degradability Rapidly degradable		

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

12.3. Bioaccumulative potential

n-hexane (110-54-3)		
Partition coefficient n-octanol/water (Log Pow) 3.9		
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)		
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component		
Talc (14807-96-6)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII	
Diphenylamine (122-39-4)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII	
Copper (7440-50-8)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII	
n-hexane (110-54-3)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII	
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII	

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

- : Disposal must be done according to official regulations.
- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Disposal must be done according to official regulations.
- : Disposal must be done according to official regulations.
- : Do not re-use empty containers.

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

HP Code

- : HP3 "Flammable:"
- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
- flammable gaseous waste: gaseous waste which is flammable in air at 20 $^{\circ}\text{C}$ and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
- HP5 "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
- HP4 "Irritant skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
- HP14 "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard	class(es)			
2.1	2.1	2.1	2.1	2.1
2 22	2	¥22	**************************************	**************************************
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Dangerous for the environment: True	Dangerous for the environment: True Marine pollutant: Yes	Dangerous for the environment: True	Dangerous for the environment: True	Dangerous for the environment: True
No supplementary information	on available			

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11 Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277 Excepted quantities (IMDG) : E0 Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2 EmS-No. (Fire) : F-D EmS-No. (Spillage) : S-U Stowage category (IMDG) : None Stowage and handling (IMDG) : SW1, SW22 Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

UK REACH Annex XVII (Restriction List)

This product contains no substance(s) listed on UK REACH Annex XVII (Restriction List) equal to or above the level of SDS disclosure

UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

UK REACH Candidate List (SVHC)

Contains no substance(s) listed on the UK REACH Candidate List

GB PIC regulation (Prior Informed Conset)

This product contains substance(s) listed on the GB PIC List equal to or above the level of SDS disclosure (Diphenylamine - 122-39-4, Annex I Part 1, Annex I Part 2)

POP Regulation (Persistent Organic Pollutants)

This product contains no substance(s) listed on the GB POP List equal to or above the level of SDS disclosure

Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

Control of Poisons and Explosives Precursors Act

This product contains no substance(s) listed as a reportable poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a reportable explosive precursor on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

Drug Precursors Regulation (273/2004)

This product contains no substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure

15.1.2. Other Information

VOC content : 460 g/l

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830 $\,$

Abbreviations and acronyms:			
EC50	Median effective concentration		
EN	European Standard		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
OEL	Occupational Exposure Limit		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
ThOD	Theoretical oxygen demand (ThOD)		
TLM	Median Tolerance Limit		
VOC	Volatile Organic Compounds		
CAS-No.	Chemical Abstract Service number		
N.O.S.	Not Otherwise Specified		
vPvB	Very Persistent and Very Bioaccumulative		
ED	Endocrine disruptor		

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aerosol 1	Aerosol, Category 1	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 2	Flammable liquids, Category 2	

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830 $\,$

Full text of H- and EUH-statements:			
H220	Extremely flammable gas.		
H222	Extremely flammable aerosol.		
H225	Highly flammable liquid and vapour.		
H229	Pressurised container: May burst if heated.		
H301	Toxic if swallowed.		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H311	Toxic in contact with skin.		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H331	Toxic if inhaled.		
H336	May cause drowsiness or dizziness.		
H361f	Suspected of damaging fertility.		
H373	May cause damage to organs through prolonged or repeated exposure.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
Press. Gas	Gases under pressure		
Repr. 2	Reproductive toxicity, Category 2		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
Skin Irrit. 2	H315	Calculation method
Aquatic Chronic 2	H411	Calculation method

Safety Data Sheet (SDS), UK

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.