

FIXING INSTRUCTIONS

Tools Required:

- Drill & 25.4mm drill bit
- Mallet
- Chisel
- Pozidrive Screwdriver
- Pencil / Marker
- Masking Tape




Fig 1. Preparation to the Door : Position the latch/deadbolt body as near to the mid height of the door as possible making sure that the proposed mortised hole avoids cutting through door frame joints. Place the latch/deadbolt body against and across the door edge and mark the top and bottom edges of the body as illustrated.




Fig 2. Along the door edge mark a vertical line center to the door thickness, which is used as a central guide line for a hole 25.4mm diameter to be drilled to the required depth. The required depth = latch/deadbolt body length+fixed forend + loose face plate. Helpful hint : Mark the " drill-bit" using adhesive tape or a suitable visible marker.




Fig 3. Insert the latch/deadbolt into the prepared mortised hole, place the loose faceplate over the fixed forend, and mark around the faceplate. Remove the latch/deadbolt and chisel out a recess to accept both fixed forend and loose faceplate, ensuring that when finally fitted the faceplate is flush with the door edge.





Fig 4. Place the body against the door face and in line with the lock recess and also making sure that allowance is made for the loose faceplate, mark and drill through the hole position for the spindle.

Fig 5. Fix the tubular latch/deadbolt complete with the loose faceplate into the door with the screws provided, ensuring the spindle passes through freely into the latch body. Fix handles, making sure to cut the spindle to the required length.

Test the final fitting ensuring that the latch/deadbolt freely operates.

Important : For tubular latches only, when fitted, check that the angled or beveled edge of the latch bolt is facing the door frame when closing. Should the latch bolt require "reversing" remove the loose faceplate, "turn the latch bolt" and refit the faceplate.




Fig 6. With the latch/deadbolt fitted and the door in the open position close the door gently against the frame and mark on the doorframe the top and bottom edge of the latch/deadbolt. For fire door application use intumescent pad (1pad per latch/lock, 1mm for 30 mins. & 2mm for 60 mins.).




Fig 7. Transfer these two marks across to the inside face of the door frame rebate. Mark an additional horizontal line approximately 2mm above the top line. This line represents the top inside edge of the aperture within the striker and will provide operating clearance. To determine the horizontal position of the striker, close the door, applying a little pressure, mark a line on the inside rebate face against the flat face of the latch/deadbolt. This line determines the outside striking edge of the "striker aperture" with final position established, place the striker in position. Mark around the outside profile of the striker and the inside edge of the aperture. Making allowance for the dust cover chisel out a recess to the required depth. Chisel out recess for the forend of the striker and dust cover, ensuring when fitted the forend is Flush with the frame. Plastic Dust Box Must Not Be Used In Fire Door Assembly.

Maintenance Instructions: Keep Lubricating with WD40 or equivalent lubricant after every 25000 cycle to ensure optimum performance.

		D.P. GARG & COMPANY PVT. LTD. B-210 B, Phase - 2, Noida - 201305 (U.P.) INDIA Phone No.: +91-120-2460071, 2460085 - 87 Fax : +91-120-2460083										25	
		2797-CPR-805686	0086-CPR-805689	BS EN 12209 : 2003	NPD	M	4	1	0	F	-		B

For Declaration of Performance please go to : www.garglocks.co.in

