


Masonry Fixings



Nylon Universal Plugs



Versatile plugs manufactured from durable nylon. Superior performance in both hollow or solid materials. Perfect for applications where there is uncertainty with regards to the type of base material.

3-
90KG

Technical Data						
Substrate	Concrete ≥25N/mm²			Plasterboard 12.5mm Thickness**		
Plug Size (mm)	6 x 30	8 x 40	10 x 50	6 x 30	8 x 40	10 x 50
Drill Hole Ø (mm)	6	8	10	6	8	10
Drill Hole Depth (mm)	40	50	60	-	-	-
Test Screw Size (mm)	4.5 x 40	5.0 x 50	6.0 x 60	3.5 x 40	4.0 x 50	4.5 x 70
Rec. Tensile Load (kN)	0.08	0.39	0.9	0.03	0.08	0.12
Max Rec. Load (kg)	8	39	90	3	8	12
Rec. Screw Ø (mm)	4.0 - 4.5	4.5 - 5.0	5.0 - 6.0	3.5	4.0	4.5
Min. Req. Screw Length (mm)*	30	40	50	40	50	60

* Add thickness of fixture to Min. required screw length.

** We do not recommend the use of power tools when fixing to plasterboard.

Product Code	Plug Size (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
TIMBAG				
224411	6.0 x 30	200	5	600
224209	8.0 x 40	100	5	600
224186	10.0 x 50	70	5	600
BAG07				
TIMPAC				
725411	6.0 x 30	20	10	50
725209	8.0 x 40	10	10	50
725185	10.0 x 50	5	10	50
PAK13				

Coach Screw & Nylon Plug

Zinc



BRICK

A traditional heavy duty woodscrew mainly used for attaching ironmongery to timber or for use with a nylon plug into masonry.

NOTE: Thread length is 2/3 of the overall length screw.
E.g. 100mm = 60mm thread.

Technical Data		
Screw Size (mm)	6.0	8.0
Socket Size (mm)	10	13
Plug Ø (mm)	10.0	12.0
Drill Hole Ø (mm)*	10.0	12.0

Product Code	Screw Size (mm)	Plug Size (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
TIMBAG					
0660CSCNB	6.0 x 60	10.0 x 50	40	5	600
0680CSCNB	6.0 x 80	10.0 x 50	30	5	600
08100CSCNB	8.0 x 100	12.0 x 60	12	5	600
BAG06					

TIMPAC					
0660CSCNP	6.0 x 60	10.0 x 50	2	5	1200
0680CSCNP	6.0 x 80	10.0 x 50	2	5	1200
08100CSCNP	8.0 x 100	12.0 x 60	2	5	4800
PAK12					

Nylon Plugs

Nylon



BRICK



Manufactured from a more durable material than standard plugs and therefore better suited for outdoor use. Often used with coach screws.

Technical Data					
Plug Ø (mm)	6.0	8.0	10.0	12.0	14.0
Drill Hole Ø (mm)*	6.0	8.0	10.0	12.0	14.0

Product Code	Plug Size (mm)	For Screw Ø (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
TIMBAG					
06NLPB	6.0 x 30	3.5 - 5.0	200	5	870
08NLPB	8.0 x 40	5.0 - 6.0	100	5	870
10NLPB	10.0 x 50	6.0 - 8.0	70	5	600
12NLPB	12.0 x 60	8.0 - 10.0	50	5	600
14NLPB	14.0 x 75	10.0 - 12.0	30	5	600
BAG07					

TIMPAC					
06NLPB	6.0 x 30	3.5 - 5.0	20	10	6000
08NLPB	8.0 x 40	5.0 - 6.0	10	10	6000
10NLPB	10.0 x 50	6.0 - 8.0	5	10	4800
12NLPB	12.0 x 60	8.0 - 10.0	2	10	4800
14NLPB	14.0 x 75	10.0 - 12.0	2	10	-
PAK13					

Metal Expansion Plugs

Yellow



BLOCK

An all steel fixing for light weight aggregate blocks. Ideal for fixing in areas such as fire escape routes where regulations restrict the use of plastic anchors or plugs.

• Conforms to BS 7671:2018



ALL STEEL
NON-FLAMMABLE FIXING

20-
50KG

Technical Data				
Substrate	Concrete Block 7N/mm²			
Plug Ø (mm)	6.0	8.0	10.0	
Drill Hole Ø (mm)	6.0	8.0	10.0	
Min. Embedment Depth (mm)	32	38	60	
Test Screw Ø (mm)	4.5	5.0	6.0	
Rec. Tensile Load (kN)	0.2	0.4	0.5	
Max Rec. Load (kg)	20	40	50	

Note: Drill hole size is relative to the compressive strength of the substrate. When fixing into concrete, the above drill hole sizes should be increased to prevent damage to the plug during installation.

Product Code	Size Ø x L (mm)	For Screw Ø (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
632MEP	6.0 x 32	4.5 - 5.0	100	18	864
838MEP	8.0 x 38	5.0 - 6.0	50	18	864
860MEP	8.0 x 60	5.0 - 6.0	50	10	500
1060MEP	10.0 x 60	6.0 - 8.0	50	10	500
MEP01					