

Stainless Steel Self-Tapping Screws

Used for stitching metal or attaching to metal. A pre-drilled hole is required. Stainless steel must be used where there is corrosive environment and/or the base material has inherent corrosive characteristics.



Pan Head (DIN7981)

A2 Stainless Steel



POZI



STEEL

THIN SHEET

Pan head for extra clamping. A2 stainless steel for ultimate resistance to corrosion.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
2965CPASS	2.9 x 6.5	PZ1	200	140	5040
2995CPASS	2.9 x 9.5	PZ1	200	140	5040
3595CPASS	3.5 x 9.5	PZ2	200	140	5040
3513CPASS	3.5 x 13	PZ2	200	75	2700
3519CPASS	3.5 x 19	PZ2	200	75	1800
3525CPASS	3.5 x 25	PZ2	200	50	1200
3938CPASS	3.9 x 38	PZ2	200	22	1056
4295CPASS	4.2 x 9.5	PZ2	200	75	2700
4213CPASS	4.2 x 13	PZ2	200	75	1800
4216CPASS	4.2 x 16	PZ2	200	38	1824
4219CPASS	4.2 x 19	PZ2	200	38	1824
4225CPASS	4.2 x 25	PZ2	200	50	1200
4232CPASS	4.2 x 32	PZ2	200	35	840
4825CPASS	4.8 x 25	PZ2	200	35	840
4832CPASS	4.8 x 32	PZ2	200	15	720
4838CPASS	4.8 x 38	PZ2	200	15	540
4850CPASS	4.8 x 50	PZ2	200	16	384
5519CPASS	5.5 x 19	PZ3	200	50	1200
5525CPASS	5.5 x 25	PZ3	200	35	840
TAS01					

Countersunk (DIN7982)

A2 Stainless Steel



POZI



STEEL

THIN SHEET

Countersunk head gives a discreet finish into pre-countersunk holes. A2 stainless steel for ultimate resistance to corrosion.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
2913CCASS	2.9 x 13	PZ1	200	140	5040
2919CCASS	2.9 x 19	PZ1	200	140	5040
3525CCASS	3.5 x 25	PZ2	200	75	2700
3995CCASS	3.9 x 9.5	PZ2	200	140	5040
3913CCASS	3.9 x 13	PZ2	200	140	5040
3925CCASS	3.9 x 25	PZ2	200	38	1824
3938CCASS	3.9 x 38	PZ2	200	50	1200
4295CCASS	4.2 x 9.5	PZ2	200	140	5040
4213CCASS	4.2 x 13	PZ2	200	75	2700
4216CCASS	4.2 x 16	PZ2	200	75	2700
4219CCASS	4.2 x 19	PZ2	200	75	1800
4225CCASS	4.2 x 25	PZ2	200	50	1200
4232CCASS	4.2 x 32	PZ2	200	30	1080
4238CCASS	4.2 x 38	PZ2	200	35	840
4819CCASS	4.8 x 19	PZ2	200	50	1200
4850CCASS	4.8 x 50	PZ2	200	15	540
TAS01					

Flange Head

A2 Stainless Steel



POZI



STEEL

THIN SHEET

Flange head gives an aesthetic finish whilst increasing the clamping ability of the screw. A2 stainless steel for ultimate resistance to corrosion.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
4295CFASS	4.2 x 9.5	PZ2	200	75	2700
4213CFASS	4.2 x 13	PZ2	200	75	1800
4219CFASS	4.2 x 19	PZ2	200	50	1200
TAS01					