

final position established mark around the Dust Box or Box Striker and drill a series of holes to the required depth removing excess wood with a chisel. Insert the dust cover and place over the striker forend (or box striker), mark around the outside of the forend and chisel the recess, ensuring the depth is sufficient for the striker face to be flush with the inside rebate frame.

Maintenance Instructions.: Keep Lubricating with WD 40 or equivalent lubricant after every 25000 cycle to ensure optimum performance.

For use on fire doors product must be fitted with intumescent pad (1mm-30min & 2mm-60min)

LOCKS

TIMCO / elite

Fitting instruction for the following


- 3 Lever Lock
- 3 Lever Bathroom lock
- 3 Lever Dead Lock
- 5 Lever Sash Lock
- 5 Lever Dead Lock
- Euro/Oval Profile Sash Lock
- Euro/Oval Profile Dead Lock
- Arch. Bathroom Lock

Tools required :


- Drill & 25.4mm drill bit
- Mallet
- Chisel
- Pozi drive Screwdriver
- Pencil/Marker
- Masking tape

Preparation to the Door.

1. Position the lock body as near to the mid height not more than 1100mm high for fire door assembly of the door as possible, making sure that the proposed morticed hole avoids cutting through doorframe joints. Place the lock body against and across the door edge and mark the top and bottom of the lock case as illustrated.



2. Along the door edge mark a vertical line central to the door thickness, which is used as a central guideline for a series of holes to be drilled to the required depth. The required depth = lock body depth+Fixed Forend & Loose Faceplate thickness.




| | | | | | | | | | | | | | | | | | | |
|-----------------------------|-----------------|-----------------|--|---|---|---|---|---|---|---|---|---|---|---|--|--|--|--|
| 25 | CE | UK CA | D.P. Garg & Company Pvt. Ltd. B-210B, Phase-2, Noida - 201305 (U.P.) India Ph. No.: +91-120-2460091, 2460085-87 Fax. 91-120 2460083 | | | | | | | | | | | | | | | |
| 3 Lever Lock | 2797-CPR-805686 | 0086-CPR-805689 | B5 EN 12209 : 2003 | 1 | M | 4 | 1 | 0 | F | 2 | K | D | 1 | A | | | | |
| 3 Lever Bathroom Lock | 2797-CPR-805686 | 0086-CPR-805689 | B5 EN 12209 : 2003 | 1 | M | 4 | 1 | 0 | F | - | B | G | 1 | 0 | | | | |
| 3 Lever Dead Lock | 2797-CPR-805686 | 0086-CPR-805689 | B5 EN 12209 : 2003 | 1 | M | 4 | 1 | 0 | F | 2 | K | D | 0 | A | | | | |
| 5 Lever Sash Lock | 2797-CPR-805686 | 0086-CPR-805689 | B5 EN 12209 : 2003 | 2 | M | 4 | 1 | 0 | F | 3 | K | D | 1 | A | | | | |
| 5 Lever Dead Lock | 2797-CPR-805686 | 0086-CPR-805689 | B5 EN 12209 : 2003 | 2 | M | 4 | 1 | 0 | F | 3 | K | D | 0 | A | | | | |
| Euro/Oval Profile Sash Lock | 2797-CPR-805686 | 0086-CPR-805689 | B5 EN 12209 : 2003 | 2 | M | 4 | 1 | 0 | F | 2 | B | A | 1 | 0 | | | | |
| Euro/Oval Profile Dead Lock | 2797-CPR-805686 | 0086-CPR-805689 | B5 EN 12209 : 2003 | 2 | M | 4 | 1 | 0 | F | 2 | B | A | 0 | 0 | | | | |
| Euro/Oval Profile Sash Lock | 2797-CPR-805686 | 0086-CPR-805689 | B5 EN 12209 : 2003 | 1 | M | 4 | 1 | 0 | F | 2 | B | A | 1 | 0 | | | | |
| Euro/Oval Profile Dead Lock | 2797-CPR-805686 | 0086-CPR-805689 | B5 EN 12209 : 2003 | 1 | M | 4 | 1 | 0 | F | 2 | B | A | 0 | 0 | | | | |
| Arch. Bathroom Lock | 2797-CPR-805686 | 0086-CPR-805689 | B5 EN 12209 : 2003 | 2 | M | 4 | 1 | 0 | F | - | B | G | 1 | 0 | | | | |


For Declaration of Performance please go to : www.garglocks.co.in

Helpful Hints - Mark the "drill-bit" using adhesive tape or a suitable visible marker. The hole centres should be slightly less than the drill diameter in order that the drilled holes overlap.


3. Chisel out the remaining wood to provide satisfactory fitment for the lock body.




4. Insert the lock body into the prepared morticed area, placing the loose face plate over the fixed forend, temporarily screw the faceplate into position and mark around the lock faceplate and chisel out a recess to accept both fixed forend and loose face plate ensuring that when finally fitted the face plate is flush with the door edge. **IMPORTANT** - With the lock fitted check that the angled or bevelled edge of the latch bolt is facing the doorframe when closing. To Reverse latchbolt remove loose faceplate & turn sash bolt for suitable handling & refix loose faceplate.



5. Place the lock body against the door face and in line with the lock recess making sure that allowance is made for the loose faceplate, mark through and drill the hole positions for the Spindle (Sashlock). Euro profile / oval profile cylinder or spindle for snib turn, key for lever lock.




6. Fix the lock complete with the loose face plate into the door with the screws provided ensuring the key, cylinder and spindle pass through freely into the lock. Fix escutcheons and or handles, making sure to cut the spindle to the required length. Test the final fitting ensuring that the Latch and / or Deadbolt freely operates.



Fixing the Box or Flat Striker

7. When the lock is fitted, with the door in the open position, turn the key to operate the dead bolt into the "locked position", gently close the door against the frame and mark on the doorframe the top edge of the latch bolt and bottom edge of the dead bolt.



8. Transfer these two marks across to the inside face of the doorframe rebate. Mark an additional horizontal line approximately 2mm above the top line. This line represents the top inside edge of the aperture within the striker and will provide operating clearance. To determine the horizontal position of the striker retract the dead bolt and close the door, applying a little pressure, mark a line on the inside rebate face against the flat face of the latch bolt. This line determines the outside striking edge of the "striker aperture". (See diagram 8). With the

