

# NITO High Pressure Couplings



Optimal solution for high-pressure cleaners and stationary installations.

NITO High Pressure Couplings are made from materials with an exceptionally strong, safety, locking mechanism that prevents leakage and accidental triggering.

Application

- NITO high-pressure coupling are top-quality products specially designed and tested for use with high-pressure water.

Connections:

3/8" female thread Range of low-pressure couplings for water.

Technical specifications:

Chrome-plated:  
Working pressure: Max. 250 bar  
Temperature: Max. 100°C

Materials:

1. Coupling body and ring are made of brass and chrome-plated
2. O-ring: NBR
3. Spring and ring are made of stainless steel
4. 8 balls made of hardened steel

Item Number	Chromium plated:
65506I3	NITO High pressure set coupling and nipple with 3/8" female BSP
65500I3	NITO High pressure coupler with 3/8" female BSP
65610I9	NITO High pressure nipple with 3/8" female BSP
65632B9	NITO High pressure Nipple with M22x1,5 female BSP without sealing bush




**Stainless steel:**  
Working pressure: Max. 390 bar  
Temperature: Max. 100°C

Materials:

1. Coupling body and ring made of AISI 304
2. O-ring: NBR\*
3. Spring and ring made of stainless steel
4. 8 balls made of hardened steel
5. Nipple made of AISI 316

\*) Viton gasket and O-ring – can be supplied as required



MAX

250 BAR

MAX

100 °C

MAX

390 BAR

MAX

160°C

Items shown represent only a small sample of our product assortment.



More NITO products

