

Pneumatic Silencers

Silencers are designed for installation on exhaust circuits to reduce the noise levels of equipment while operating, thus improving user comfort.

WARNING: This product can expose you to chemicals including Carbon black (airborne, unbound particle) which is known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov



Temperature Standards:

-20°C to +180°C



Maximum Operating Pressure:

12 bar

316L Stainless Steel Body, BSPP

Part Code	Thread
LE-0672 00 10	1/8"
LE-0672 00 13	1/4"
LE-0672 00 17	3/8"
LE-0672 00 21	1/2"
LE-0672 00 27	3/4"
LE-0672 00 34	1"

316L Stainless Steel Body, NPT

Part Code	Thread
LE-0683 00 11	1/8"
LE-0683 00 14	1/4"
LE-0683 00 18	3/8"
LE-0683 00 22	1/2"

Qty per box: 5

Weight: 0.007 kg

Application: Robotics, Textile, Semi-Conductors, Packaging, Pneumatics

Media: Compressed air

Specifications Met: DI: 2002/95/EC (RoHS), RG: 1907/2006 (REACH), DI:90/23/EC (PED), DI: 2003/10/EC (Noise Directive) Requirement to use ear protection if exposure > 8 hours (85 dBA), RG: 1910.95(b) (OSHA) Requirement to use ear protection if exposure > 8 hours (90 dBA)