

Wash Down Equipment

EPDM, abrasion and weather conditions

One or two high tensile steel braided reinforcement, synthetic rubber resistant to water and detergents

Blue Cold Water Pressure Washer Hose

 **Working Temperature:**
-40°C to +100°C



Black Cold Water Pressure Washer Hose

 **Working Temperature:**
-40°C to +100°C



DESCRIPTION	SIZE			ID		OD		WP		PP		BP		BR	
	MM	INCH	SAE	MIN	MAX	MIN	MAX	MPA	PSI	MPA	PSI	MPA	PSI	INCH	MM
CWBLUE-50-R1/CWBLACK-50-R1															
CW****04-50-R1	6.3	1/4"	-04	6.2	7.0	13.4	14.1	19.2	2780	39	5580	77	11165	3.94	100
CW****05-50-R1	8	5/16"	-05	7.7	8.5	15	15.7	17.5	2540	35	5075	70	10150	4.53	115
CW****06-50-R1	10	3/8"	-06	9.3	10.1	17.4	18.1	15.7	2280	32	4570	63	9135	4.92	130
CWBLUE-50-R2/CWBLACK-50-R2															
CW****04-50-R2	6.3	1/4"	-04	6.2	7.0	15.0	15.7	35	5075	70	10150	140	20300	3.94	100
CW****05-50-R2	8	5/16"	-05	7.7	8.5	16.6	17.3	29.7	4310	60	8630	119	17255	4.53	115
CW****06-50-R2	10	3/8"	-06	9.3	10.1	19.0	19.7	28	4060	56	8120	112	16240	4.92	130