## **Penetrating Oil**

# making the difference

### **Technical Data**

**PENETRATING OIL FG** is specifically developed for the food industry. It rapidly penetrates to loosen rust and scale to free corroded fasteners and mechanical components. Eases disassembly of mechanical equipment, fittings and assemblies. Can be used in areas where incidental contact with food may occur.

#### **FEATURES**

- NSF H1 registered (N° 140260) for use in the food industry
- Penetrates deep into threads quickly
- Frees metal parts seized by dirt, rust, corrosion or dried-up greasy deposits
- Assists quick disassembly of mechanical components, fittings, assemblies, nuts and bolts and other close tolerance fasteners
- Reduces scrap rate of seized parts
- Does not contain silicones
- Safe for all metals and for most plastics and rubbers

#### **TECHNICAL DATA**

NSF Registered, Category : H1 (N° 140260)

Appearance : Dark grey liquid

Odour Hydrocarbon

Specific Gravity (@ 20°C) : 0.76

Pressure @ 25°C 2.7 Bar

Discharge Rate : 1.3 g/sec

Solubility : Soluble in solvents, insoluble in water and alcohol

Flammability : Classified as extremely flammable under current EC Regulations

Flashpoint : Not applicable in sealed aerosol

Packaging : 400ml Aerosol

Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives



**PART NUMBER:** 6150003600









#### **STORAGE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below  $50^{\circ}$ C, away from direct heat and naked flame.

#### **HEALTH AND SAFETY**

Health and Safety sheet available separately.

#### MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.