

# Liquid Level Gauges



## EcoFit Gauges

EcoFit liquid level gauges are available up to 1 metre, each gauge above 400mm is supplied with a upper tank bracket. Thread sizes available in G1/4", G3/8", G1/2" BSPP Male

- Suitable for many industrial & domestic usages, subject to pressure & material compatibility.

**Pressure:** Atmospheric.

**Lower Body:** Brass, nickel plated.

**Fixing Bolts:** Brass, nickel plated.

**Seals:** FKM.

**Sight Tube:** Polycarbonate.

**Guard Tube:** Polycarbonate.

**Top Cap:** Brass.

**Adaptor:** Brass.

**Tank Seals:** Walkertite washer.



### Eco fit liquid level gauge

The Eco-fit liquid level gauge is of atmospheric design, meaning that it has a bottom valveless connection, while the top is atmospheric venting. Suitable for atmospheric conditions only, but has a upper temperature range of 63°C. Available in G1/4" (also available with adaptors to increase connection size to G3/8" BSP-P and G1/2" BSP-P)

The bottom banjo connection is G1/4" BSP manufactured in Stainless Steel the Sight tube is polycarbonate Plastic, (Not available in Glass), the outer protector guard tube is also polycarbonate which offers 360° visibility. Available up to 1000mm long.

**Connection:** G1/4" - G1/2" BSP Male

**Operating pressure:** Atmospheric pressure

**Maximum temperatures:** +65°C

**Length (mm):** 100 - 1000 (Over 400mm centres is supplied with a upper tank bracket, it can also be manufactured to special lengths. Contact our technical sales department for details)

**Lower body, fixing bolt material:** Nickel Plated Brass or Stainless Steel

**Seal material:** FKM

**Sight & guard tube material:** Polycarbonate Plastic

**Adaptor material:** Brass