



S/666, S/667
3/2 poppet valves
mechanically and manually actuated
G1/8

Long established and well-proven valves
Compact size
Normally closed and normally open models
May also be used as 2/2 valves



Technical features

Medium:
 Compressed air, filtered,
 lubricated and non-lubricated
 or hydraulic fluid
Operation:
 Poppet valves, directly actuated
Mounting:
 Through-holes in valve body

Operating pressure:
 2 ... 10 bar
Port size:
 G1/8
Fluid/Ambient temperature:
 +5 ... 80°C

Flow (to CETOP RP50P):
 l/min Cv
 S/666/.. 0,174 0,20
 S/667/.. 0,156 0,18
Others:
 For use as a 2/2 valve the main
 supply must be connected to
 port '1' and the exhaust port '3'
 should be plugged.

Materials:
 Body: Diecast zinc alloy
 Piston: aluminium
 Seals: NBR


Technical data
3/2 mechanical valves

Symbol	Port size	Function	Operator/Return	Operating pressure (bar)	Operating force or torque at 6,3 bar	Weight (kg)	Spares Kit	Dimension No.	Model
	G1/8	NC	Plunger/Spring	2 ...10	35 N	0,20	QS/666/1/00	1	S/666/14
	G1/8	NO	Plunger/Spring	2 ...10	72 N	0,20	QS/667/1/00	1	S/667/14
	G1/8	NC	Roller/Spring	2 ...10	20 N	0,30	QS/666/1/00	2	S/666/8
	G1/8	NO	Roller/Spring	2 ...10	40 N	0,30	QS/667/1/00	2	S/667/8
	G1/8	NC	Roller/Spring	2 ...10	0,25 Nm	0,30	QS/666/1/00	3	S/666/108
	G1/8	NC	Rod/Spring	2 ...10	0,25 Nm	0,30	QS/666/1/00	4	S/666/106
	G1/8	NC	Antenna/Spring	2 ...10	0,25 Nm	0,30	QS/666/1/00	5	S/666/116

3/2 manual valves


Symbol	Port size	Function	Knob colour	Operator/Return	Operating pressure (bar)	Operating force or torque at 6,3 bar	Weight (kg)	Spares Kit	Dimension No.	Model
	G1/8	NC	Silver	Knob/spring	2 ...10	35	0,20	QS/666/1/00	7	S/666/1
	G1/8	NC	Black	Knob/spring	2 ...10	35	0,20	QS/666/1/00	7	S/666/1N
	G1/8	NC	Red	Knob/spring	2 ...10	35	0,20	QS/666/1/00	7	S/666/1R
	G1/8	NC	Green	Knob/spring	2 ...10	35	0,20	QS/666/1/00	7	S/666/1G
	G1/8	NC	—	Lever/lever (Panel mounting)	2 ...10	14	0,30	QS/666/1/00	8	S/666/7
	G1/8	NC	—	Lever (long)/lever (Panel mounting)	2 ...10	10	0,30	QS/666/1/00	6	S/666/117

5




*Rotation at Point of Application: 40° minimum @ 80 mm
50° minimum @ 120 mm
55° minimum @ 160 mm
Mechanism may be operated either side of centre line.

6




Panel hole: \varnothing 16 mm
Panel thickness: 4 mm maximum

7



8



Panel hole: \varnothing 16 mm
Panel thickness: 4 mm maximum

Warning

These products are intended for use in industrial compressed air systems only. Do not use these products where pressures and temperatures can exceed those listed under 'Technical features'.

Before using these products with fluids other than those specified, for non-industrial applications, life-support systems, or other applications not within published specifications, consult NORGREN.

Through misuse, age, or malfunction, components used in fluid power systems can fail in various modes.

The system designer is warned to consider the failure modes of all component parts used in fluid power systems and to provide adequate safeguards to prevent personal injury or damage to equipment in the event of such failure.

System designers must provide a warning to end users in the system instructional manual if protection against a failure mode cannot be adequately provided.

System designers and end users are cautioned to review specific warnings found in instruction sheets packed and shipped with these products.