






Specification			3	5	5
Working (bor)	Oil ports P.A.B	3	350	31	15
pressure (bar)	Oil ports T	1	00	10	00
Max. Flow	(L/min)	8	30	12	20
Working fluid		Mineral oil;phosphate-ester			
Fluid temp.	(°C)	-20~70			
Viscosity	(mm²/s)	2.8~100			
Working ()	DC	12		24	
voltage (V	AC	110/	50Hz	220/	50Hz
Max.Switch frequency (T/h)		15000	(DC)	7200 ((AC)
Insulation gra	de		IP	65	
Maiabt (I.a.)	Single solenoid	1.45(DC)	1.4(AC)	5.1(DC)	4.3(AC)
Weight (kg)	Double solenoids	1.95(DC)	1.9(AC)	6.7(DC)	5.1(AC)
Cleanliness	should be a NAS1638.It	ne maximum allowable cleanliness of the oil could be according to 9th degree of Standard AS1638.It is suggested that the minimum ter rating should be β10≥75.			





Code symbol

Spring Return 3 Position

Spring Return 2 Position


$$B = \begin{array}{c} AB \\ b \\ \top \\ \top \\ \top \end{array}$$

Detent

$$D = a \longrightarrow_{P \to T} b$$




Name of solenoid



- 1. a When movement a, $P \rightarrow A B \rightarrow T$
- 2. b When movement b, $P \rightarrow B A \rightarrow T$
- 3. Oil flow in the opposite direction with the above–mentioned movement for 3GY symbol Valve.

Size 3 Specification Performance curve (Measured at $v = 41 \text{mm}^2/\text{s}$ and $t = 50 ^{\circ}\text{C}$)



Function	Direction			
code	P→A	P→B	A→T	B→T
2H	1	1	3	1
2B3	1	1	3	1
2B2 2B2L	5	5	3	3
2D	2	5	3	3
3E	3	3	1	1
3G	6	6	9	9
3H	2	4	2	2
3J	1	1	2	1




(The working limits for directional valves have determined by using solenoids at their operating temperature, 10% under voltage and with no pre-loading of the tank)

With regard to the four—way valve, the normal flow data as shown is get from the regular use of two directions of the flow (e.g.P to A,and simultaneous return flow from B to T). See tables. If only one flow direction is needed, for example: When a four port valve which is closed up port A or port B, used as a three—way valve, the Maximum flow may be very small in the serious condition.


DC Solenoid operation DC D24, D1 2, B220, B110		AC Solenoid operation AC A110, A220, 50HZ	
Curve	Symbol	Curve Symbol	
5	3J	15	3G
6	3G 3H	16	3H
8	2H 2D	17	3J 3E
10	3E 2D	18	2D 2C 2E
	2C 2E		

Working pressure(MPa)




- 1) No manual emergency operation
- 2) Oil return from actuator to oil tank

Working pressure(MPa)





Size 5 Specification Performance curve (Measured at $v = 41 \text{mm}^2/\text{s}$ and $t = 50 ^{\circ}\text{C}$)




Etion	Direction			
Function code	P→A	P→B	A→T	B→T
2H 2D	2	2	3	3
2E 2C 3E	2	2	4	4
3G	3	3	4	6
ЗН	1	1	4	5




(The working limits for directional valves have determined by using solenoids at their operating temperature, 10% under voltage and with no pre-loading of the tank)

With regard to the four—way valve, the normal flow data as shown is get from the regular use of two directions of the flow (e.g.P to A, and simultaneous return flow from B to T). See tables. If only one flow direction is needed, for example: When a four port valve which is closed up port A or port B, used as a three—way valve, the Maximum flow may be very small in the serious condition.




Curve	Symbol
1	2DY 2HY 2DD
2	2E 2C 3EY
3	3JY
4	3HY
6	3GY

Working pressure(MPa) AC solenoid operation




110V, 50Hz; 120V, 60Hz; 220V, 50Hz; 240V, 60Hz;			
Curve	Curve Symbol		
1	2DY 2HY 2DD		
2	2E 2C 3EY		
5	3JY		
6	3GY		
9	3HY		

Working pressure(MPa) AC solenoid operation






External dimensions (Size 3 Direct current plug type)




External dimensions (Size 3 Direct current wire box type)






External dimensions (Size 3 Alternating current plug type)




External dimensions (Size 3 Alternating current wire box type)






Size 3 of subplate oil port




External dimensions (Size 3 Direct current plug type)






External dimensions (Size 5 Alternating current plug type)



Size 5 of subplate oil port



Modular flow control valve




Technical specification



Specification		3	5	
Max.pressure	(MPa)	31.5		
Max.flow	(L/min)	30 50		
Hydraulic fluid		Mineral oil;phosphate-ester		
Fluid temp	$(^{\circ}\!\!\!C)$	-20~70		
Viscosity	(mm^2/s)	2.8~380		
Opening pressure (MPa)		a: 0.05		
Cleanliness	should b NAS163	ximum allowable cleanliness of the oil be according to 9th degree of Standard 38.It is suggested that the minimum ting should beβ10≥75.		

Model instruction AFR * * * * /Design/ * * **Flow Restrictor** Seals Blank = NBR**Specification** V = FKMISO Size 3 ISO Size 5 Control Fine = 1QMeter Standard = 2Q Meter In = XMeter Out = Y Design **Throttle** Rexroth = RX14A & B = BlankB Port = B**Adjustment Type** A Port = A2 - Hand Knob (STD) P P ort = P

Code symbol










External dimensions


AFR 3 Y





AFR 3 X






Notice: The surface, connecting with the valve, should be Ra0.8 roughness, and 0.01/100mm flatness.






External dimensions

AFR 5 Y






Notice: The surface, connecting with the valve, should be Ra0.8 roughness, and 0.01/100 mm flatness.






External dimensions

AFR 5 X





 $Notice: \ The surface, connecting with the valve, should be Ra0.8 \ roughness, and 0.01/100mm \ flatness.$



Modular pilot-operated check valve




Technical specification


Specification		3	5
Max. working pressure (bar)		315	
Max. Flow	(L/min)	60	100
Working fluid		Mineral oil;phosphate-ester	
Fluid temp.	$(^{\circ}\!$	-20~70	
Viscosity	(mm^2/s)	2.8~500	
Opening pressure (MPa)		a0.05 b0	.25 c0.4
Cleanliness	The maximum allowable cleanliness of the oil should be according to 9th degree of Standard NAS1638.It is suggested that the minimum		

filter rating should be β 10 \geqslant 75.

Model description




Code symbol






Modular pilot-operated check valve

Size 3 External dimensions



Size 5 External dimensions



Modular reducing valve




Technical specification




Specification		3	5
Max. working pressure (bar)		210	
Max. Flow	(L/min)	35	70
Working fluid		Mineral oil;phosphate-ester	
Fluid temp.	$(^{\circ}\!$	-20~70	
Viscosity	(mm^2/s)	12~380	
Cleanliness	The maximum allowable cleanliness of the oil should be according to 9th degree of Standard NAS1638.It is suggested that the minimum filter rating should be β10≥75.		

Model description




Code symbol








Size 3 External dimensions







Size 5 External dimensions








Technical specification




Specification		3	5
Max. working pressure (bar)		315	
Max. Flow	(L/min)	35	70
Working fluid		Mineral oil;phosphate-ester	
Fluid temp.	(℃)	-20~70	
Viscosity	(mm²/s)	12~380	
Cleanliness	The maximum allowable cleanliness of the oil should be according to 9th degree of Standard NAS1638.It is suggested that the minimum filter rating should be β 10≥75.		

Model description



Code symbol







Size 3 External dimensions

ASPR 3 AT <u>4-Φ5.5 Thr</u>u hole ФТ 32.5 $A \rightarrow \Phi$ 46 7.5 13 Φ 4Depth 4.2 10.3 27.8 40.5 100 210.5~203 ASPR 3 BT + PT <u>4-Ф5.5 Thr</u>u hole ФТ 10.3 Φ4 Depth4.2 27.8 210.5~203





Size 5 External dimensions

