



Thermoplastic Sewer Jetting Hose 2,500 PSI

Thermoplastic Sewer Jetting Hose 210 bar

Application:

Standard Sewer Cleaning vehicles and cleaning equipment. Special construction for optimum cut and wear resistance. Bonded tube and cover. Available in long lengths with a special cover resistant to microbiological degradation. Lightweight compared to conventional rubber alternatives and increased lifetime.

Application Standards:

Exitflex QD-M

Construction:

Core: Thermoplastic Elastomer

Reinforcement: 1 or 2 braids of synthetic fibre

Cover: Orange colour - polyurethane.


Other lengths and pressure ratings are available on request.



Temperature Standards:
-40°C to +60°C



Maximum Working Pressure:
175 bar



Hose Type	Size		Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Ref. Nr.	Dash Size	DN	in inch	in mm	in inch	in mm	in psi	in bar	in psi	in bar	in mm	in inch
EF302-6	6	10	3/8	9.6	0.650	16.5	3.000	210	7.500	525	75	3.0
EF302-8	8	12	1/2	12.7	0.880	22.4	3.000	210	7.500	525	100	4.0
EF302-12	12	20	3/4	19.1	1.250	31.8	3.000	210	7.500	525	125	5.0
EF302-16	16	25	1	25.4	1.525	38.7	3.000	210	7.500	525	160	6.4
EF302-20	20	32	1.1/4	32.0	1.840	46.7	3.000	210	7.500	525	250	10.0