

# Interchange Range

## XF Couplings



Offers excellent flow characteristics providing the workshop with increased airflow when required and enhanced tool efficiency. Designed and manufactured in Sheffield by PCL.

### Key Product Benefits

- **High flow rate** - 130cfm @ 100lbf/in<sup>2</sup>
- Offers enhanced tool efficiency
- Steel construction with corrosion resistant finish for longer life
- Steel shoulder prevents accidental disconnection

### Specifications

|                          |                          |        |
|--------------------------|--------------------------|--------|
| Nominal bore             | 7.4 mm                   |        |
| Flow rate @ 6bar         | 2200 l/min @ 0.5bar p.d. |        |
| Maximum Working Pressure | 500 lbf/in <sup>2</sup>  | 35 bar |
| Interchangeability       | Rectus 25/26             |        |
|                          | Legris 25/26             |        |
|                          | Norgren 234/238          |        |
|                          | Schrader InterCheck 35   |        |

### Product Options

| Part No. | Description | Thread Type    | Thread Size |
|----------|-------------|----------------|-------------|
| AC71CM   | XF Coupling | Male           | R 1/4       |
| AC71EM   | XF Coupling | Male           | R 3/8       |
| AC71JM   | XF Coupling | Male           | R 1/2       |
| AC71CF   | XF Coupling | Female         | Rp 1/4      |
| AC71EF   | XF Coupling | Female         | Rp 3/8      |
| AC71JF   | XF Coupling | Female         | Rp 1/2      |
| AC7106   | XF Coupling | Hose Tailpiece | 6mm         |
| AC7108   | XF Coupling | Hose Tailpiece | 8mm         |
| AC7109   | XF Coupling | Hose Tailpiece | 9mm         |
| AC7110   | XF Coupling | Hose Tailpiece | 10mm        |
| AC7113   | XF Coupling | Hose Tailpiece | 13mm        |
| AC7113   | XF Coupling | Hose Tailpiece | 13mm        |