

# ACTUATION LIMIT SWITCH BOXES



## Specification

- 1 Model KLS-820M.
- 2 Enclosure: weatherproof IP67.
- 3 Solid and compact design.
- 4 Bolts on visual position indicator (re-adjustment available upon required direction).
- 5 Dual cable entries: 2 x 1/2" NPT (Standard) M20, PG13.5, PF1/2", PF1/2" (option).
- 6 Terminal strips: 8 points (0.08 – 2.5mm<sup>2</sup>).
- 7 Captive cover Bolts.
- 8 Easy mounting.
- 9 NAMUR standard stainless steel shaft and bracket.

## Material

<b>Housing Cover &amp; Body</b>	Aluminium Die Cast
<b>Shaft</b>	Stainless Steel
<b>Indicator Cover</b>	Polycarbonate
<b>Cam</b>	Polycarbonate
<b>Spring</b>	Stainless Steel
<b>Housing Cover Bolt</b>	Stainless Steel
<b>O-ring</b>	NBR
<b>Bushing</b>	Bronze
<b>E-ring(shaft)</b>	Stainless Steel
<b>Earth Lug</b>	Stainless Steel
<b>Indicator</b>	ABS/Polycarbonate
<b>Bracket</b>	Stainless Steel

## Position Monitor

- 1 Continuous visual position indicator.
- 2 Made of high impact, heat, chemical resistance and transparent carbonate.
- 3 Excellent corrosion protection, high visibility and reliability

## Dimensions

