



# Bundy Tube

Copper Tube Double Walked with Low Carbon Steel Zinc Plating

**Tube Operating Temperature:**  
-40°C+120°C

Uses brake systems refrigeration units gas pilot supply lines or high heat industrial application



## Imperial

| Part Code       | Old Part Code | Tube O.D. Size | Wall Thickness inches | Burst Pressure PSI | Length Metres |
|-----------------|---------------|----------------|-----------------------|--------------------|---------------|
| <b>FT-BTI03</b> | BTI03         | 3/16"          | 0.028"                | 16500              | 3.2M          |
| <b>FT-BTI04</b> | BTI04         | 1/4"           | 0.028"                | 12000              | 3.2M          |
| <b>FT-BTI05</b> | BTI05         | 5/16"          | 0.028"                | 10875              | 3.2M          |
| <b>FT-BTI06</b> | BTI06         | 3/8"           | 0.028"                | 8200               | 3.2M          |

## Metric

| Part Code       | Old Part Code | Tube O.D. Size | Wall Thickness inches | Burst Pressure PSI | Length Metres |
|-----------------|---------------|----------------|-----------------------|--------------------|---------------|
| <b>FT-BTM06</b> | BTM06         | 6MM            | 0.028"                | 13500              | 3.2M          |
| <b>FT-BTM08</b> | BTM08         | 8MM            | 0.028"                | 10875              | 3.2M          |
| <b>FT-BTM10</b> | BTM10         | 10MM           | 0.028"                | 7500               | 3.2M          |