

# Hydraulic Filtration



## Tank Top Filters



### Tanktopper Series I, II & III

Tanktop mounted return line filters with integrated air breather, max. 650 l/min - 10 bar

#### Product Features

- Tanktopper offers a total filtration solution with integrated air breather.
- Patented LEIF® elements safeguard filtration quality.
- Maximum pressure 10 bar. Maximum flow 650 l/min.
- In-to-Out filtration plus gauge and switch options.

#### Technical Specifications

##### Product Description:

Tank top mounted, return filter with aluminium head and co-polymer cover

**Maximum Working Pressure:** 10 bar

**Operating Temperature Range:** -40°C to +80°C

**Seal Material:** Nitrile, fluoroelastomer (on request)

**Bypass Setting:** Opening pressure 1.5

##### Connections:

Threaded BSP or SAE ports. Second return port available for Tanktopper II and Tanktopper III

**Filtration Media:**\* 10 micron Microglass III, Ecoglass III for LEIF® element. Air breather 10 micron Abs

**Magnetic Pack Options:** Optional for Tanktopper I.

Standard for Tanktopper II and III

**For more information see the HFDE product catalogue Ref: FDHB500.**

Part Number	Flow L/Min	Bypass	Ports	Included Options	Replacement Elements
TPR110QLBP2EG12E	40	1.5 bar	G¾"	Magnets	937902Q
TPR510QLBP2E2G201	120	1.5 bar	2x G1¼"	None	937892Q
TPR710QLBP2E2G241	250	1.5 bar	2x G1½"	None	937894Q

\*Note: All filter assemblies are supplied with plugged indicator ports. Indicator codes are shown on Page 10. Indicators can be ordered separately from the filter assembly. 10 micron element options have been selected for all filter products in this overview except EPF, DF40 and Eco 130 Series filters.