W Range Solder Ring Fittings





GENERAL RANGE

- Fittings are manufactured from copper and copper alloy
- Available in sizes from 8-54mm
- Fittings are designed for jointing copper tubes to BS EN 1057 in hot and cold water services, in small bore and minibore central heating, low pressure steam heating, and in vented and unvented closed circuit heating systems
- WRAS approved.
- Manufactured to BS EN 1254 Part 1

	Size
MSR1 Straight coupling copper x copper	8mm 10mm 15mm 22mm 28mm 35mm 42mm
MSR1IM Slip coupling adaptor. Imperial x metric copper x copper. To connect imperial tube to metric tube	1/2" x 15mm 3/4" x 22mm

MSR1R Reducing coupling copper x copper

15 x 8mm 15 x 10mm 22 x 15mm

MSR15 Straight coupling, slip pattern copper x

15mm

28 x 22mm

MSR2 Straight female connector copper x BSP parallel female thread

22mm x 3/4"



MSR3 Straight male x BSP taper male thread



22mm x 3/4" 28mm x 1" 35mm x 1.1/4" 42mm x 1.1/2"

MSR6 Reducer larger end for insertion into fitting

10 x 8mm

15 x 8mm 15 x 10mm 22 x 15mm 28 x 15mm

28 x 22mm 35 x 15mm 35 x 22mm 35 x 28mm 42 x 15mm 42 x 22mm

42 x 28mm

54 x 15mm

54 x 22mm 54 x 28mm 54 x 35mm

54 x 42mm

MSR12 Elbow copper



8mm 10mm 15mm 22mm 28mm 35mm 54mm

MSR12S Street elbow copper for insertion into



22mm 28mm

MSR13 Male elbow copper x BSP taper male

15mm x 1/2"

15mm x 1/2"



copper x BSP parallel female thread. Triangular backplate three hole fixing

copper x copper

15mm 22mm 28mm 35mm 42mm 54mm

MSR24 Equal tee all ends



10mm 15mm 22mm 28mm 35mm 42mm 54mm

MSR25 Tee, reduced branch all ends for copper



22 x 22 x 15mm 28 x 28 x 15mm 28 x 28 x 15mm 28 x 28 x 22mm 35 x 35 x 15mm 35 x 35 x 22mm 35 x 35 x 22mm 35 x 35 x 22mm 42 x 42 x 15mm 42 x 42 x 22mm 42 x 42 x 23mm 54 x 54 x 21mm 54 x 54 x 22mm 54 x 54 x 28mm 54 x 54 x 35mm 54 x 54 x 42mm

MSR26 Tee, one end reduced all ends for copper

22 x 15 x 22mm 28 x 15 x 28mm 28 x 22 x 28mm



MSR27 Tee, one end and branch reduced all ends for copper

22 x 15 x 15mm 28 x 22 x 15mm 28 x 22 x 22mm



MSR28 Tee, both ends reduced all ends for

15 x 15 x 22mm



MSR30 Female tee copper ends x BSP parallel female branch 15 x 15mm x 1/2"



MSR61 Stop end for use on copper tube

8mm 10mm 15mm



MSR62 Tap connector copper x BSP union nut. Spigot and washer joint

15mm x 1/2" 15mm x 3/4" 22mm x 3/4"



MSR63 Bent tap connector copper x BSP union nut. Spigot and

15mm x 1/2"



MSR64 Bent union adaptor copper x BSP union nut. Cone joint to BS 1010

22mm x 1"



MSR68 Union adaptor copper x BSP union nut Cone joint to BS 1010

22mm x 1"





E Range End Feed Fittings

GENERAL RANGE

- Designed for end-feeding with soft solder or hard solder
- Available in sizes from 8-54mm, ideal for use in hot and cold water services, central heating, fuel services and general engineering applications
- WRAS approved.
- Manufactured to BS EN 1254 Part 1

MEF1 Straight coupling copper x copper

8mm 10mm 15mm 22mm 28mm 35mm 42mm 54mm

MEF1IM Adaptor coupling imperial copper x metric copper.
To connect imperial tube to metric tube

1/2" x 15mm 3/4" x 22mm



MEF1R Reducing coupling copper x copper 10 x 8mm 15 x 10mm 22 x 15mm



28 x 15mm 28 x 22mm



MEF2 Straight female connector copper x BSP parallel female thread

15mm x 1/2" 22mm x 3/4" 28mm x 1"



MEF3 Straight male connector copper x BSP taper male thread

15mm x 1/2" 22mm x 3/4" 28mm x 1" 35mm x 1 1/4" 42mm x 1 1/2" 54mm x 2"



MEF6 Reducer larger end male copper for insertion into fitting x female copper



15 x 10mm 22 x 15mm 28 x 15mm 28 x 22mm 35 x 15mm 35 x 22mm 35 x 28mm 42 x 15mm 42 x 22mm 42 x 28mm 42 x 35mm 54 x 15mm 54 x 22mm 54 x 28mm 54 x 35mm 54 x 42mm

10 x 8mm 15 x 8mm

MEF12 Elbow copper

8mm 10mm 15mm 22mm 28mm 35mm 42mm 54mm

MEF12S Street elbow female copper x male copper for insertion into fitting



10mm 15mm 22mm 28mm 35mm 42mm 54mm

MEF13 Male elbow copper x BSP taper male thread 22mm x 3/4"



MEF14 Female elbow copper x BSP parallel female thread 15mm x 1/2" 22mm x 3/4"



MEF15 Backplate elbow. Copper x BSP parallel female thread. Backplate with three hole fixing

15mm x 1/2"



MEF21 Obtuse elbow, 45°

15mm 22mm 28mm 35mm 42mm 54mm

MEF21S Obtuse street elbow, 45° female copper x male copper for insertion in fitting

15mm 22mm 28mm 35mm 42mm



MEF22 Partial crossover female copper x male copper for insertion in fitting

15mm



MEF23 Full crossover copper x copper

15mm



MEF24 Equal tee, all ends for copper



8mm 10mm 15mm 22mm 28mm 35mm 42mm 54mm

MEF25 Tee, reduced branch, all ends for



15 x 15 x 10mm 22 x 22 x 15mm 28 x 28 x 15mm 28 x 28 x 22mm 35 x 35 x 15mm 35 x 35 x 22mm 35 x 35 x 28mm 42 x 42 x 15mm 42 x 42 x 22mm 42 x 42 x 22mm 42 x 42 x 28mm 42 x 42 x 35mm 54 x 54 x 15mm 54 x 54 x 22mm 54 x 54 x 28mm 54 x 54 x 35mm 54 x 54 x 35mm 54 x 54 x 42mm

MEF26 Tee, one end reduced, all ends for

22 x 15 x 22mm 28 x 15 x 28mm 28 x 22 x 28mm 35 x 22 x 35mm 35 x 28 x 35mm



28 x 15 x 15mm 28 x 15 x 22mm 28 x 22 x 15mm 28 x 22 x 22mm 35 x 28 x 15mm 35 x 28 x 28mm

42 x 35 x 35mm 54 x 42 x 42mm

MEF28 Tee, both ends reduced, all ends for

15 x 15 x 22mm



MEF61 Stop end for use with copper tube



15mm 22mm 28mm 35mm 42mm

MEF61AV Air release stop end. Female end for use on copper



MEF62 Straight tap connector copper x BSP hexagonal union nut. Spigot and washer joint

15mm x 1/2" 15mm x 3/4" 22mm x 3/4"



MEF63 Bent tap connector copper x BSP hexagonal union nut. Spigot and washer joint

15mm x 1/2" 15mm x 3/4" 22mm x 3/4"



MEF64 Bent union adaptor copper x BSP union nut.
Cone joint to BS 1010. Supplied with bent copper tail



MEF68 Straight union adaptor copper x BSP union nut. Cone joint to BS 1010

28mm x 1 1/4"





Compression Fittings

K600 BRASS COMPRESSION FITTINGS

- Non-manipulative (type A) duplex brass compression fittings in sizes from 8-54mm
- Suitable for use on closed circuit central heating systems, in above ground hot and cold water services, on compressed air lines and other fluids and low pressure gas services
- WRAS approved.
- Manufactured to BS EN 1254 Part 2

MC301 Straight coupling



8mm 10mm 15mm 22mm 28_{mm} 35mm 42mm 54mm

10 x 8mm 15 x 8mm 15 x 10mm 15 x 12mm 22 x 15mm 28 x 22mm

MC301BP Burst repair coupling copper x copper 15 x 15 x 80mm



MC302 Male coupling copper x BSP parallel male thread



10 x 1/4" 10 x 3/8" 10 x 3/6 10 x 1/2" 22 x 1/2" 22 x 3/4" 15 x 1/4" 22 x 1" 28 x 3/4" 28 x 3/4" 15 x 3/8" 28 x 1" 15 x 1/2" 28 x 1.1/4" 35 x 1" 15 x 3/4" 35 x 1.1/4" 42 x 1.1/2" 54 x 2"

8 x 1/4"

MC303 Female coupling copper x BSP parallel female thread



10mm x 3/8" 10mm x 1/2" 15mm x 1/4" 15mm x 3/8" 15mm x 1/2" 15mm x 3/4" 22mm x 1/2" 22mm x 3/4" 22mm x 1" 28mm x 1" 35mm x 1.1/4" 42mm x 1.1/2 54mm x 2"

8mm x 1/4" 10mm x 1/4"

MC401 Elbow copper 8mm 10mm 15mm 22mm 28mm 35mm 42mm 54mm MC402 Male elbow copper x BSP parallel male thread 15mm x 1/2" 22mm x 3/4" 22mm x 1" 28mm x 1" 35mm x 1.1/4" 42mm x 1.1/2" 54mm x 2" MC403 Female elbow copper x BSP parallel female thread 15mm x 1/2" 15mm x 3/4" 15mm x 3/4" 22mm x 3/4" 22mm x 1" 28mm x 3/4" 28mm x 1" 35mm x 1.1/4" 42mm x 1.1/2" 54mm x 2' MC403W Backplate elbow copper x BSP parallel female thread with 15mm x 1/2" 22mm x 3/4" MC601EQ Equal tee, all ends for copper 10mm 15mm 22mm 28mm

35mm 42mm 54mm MC601 Tee both ends 15 x 15 22mm



MC601 Tee, one end reduced, all ends for 22 x 15 x 22mm 28 x 15 x 28mm 28 x 22 x 28mm copper



MC601 Tee, with reduced branch, all ends for 22 x 15mm 28 x 15mm 28 x 22mm copper



MC601 Tee, one end and branch reduced, all ends for copper 22 x 15 x 15mm



MC303SF Straight swivel tap connector. copper x union nut. Spigot and fibre washer joint

15mm x 1/2" 15mm x 3/4" 22mm x 3/4"



MC403SF Bent swivel tap connector, copper x union nut. Spigot and fibre washer joint

15mm x 1/2" 22mm x 3/4"



MC684 Tee CxF end

15mm x 1/2"



MC617 Tee CxF branch

15mm x 1/2" 22mm x 1/2" 22mm x 3/4"



MC68 Reducing set for reducing the size of a Kuterlite socket. N.B. Only one reducing set can be used per end

10 x 8mm 15 x 8mm 15 x 10mm 15 x 12mm 22 x 15mm 28 x 15mm

28 x 22mm



MC321 Tank connector copper end with flange and backnut

22mm 28mm 35mm 42mm 54mm

15mm



MC323 End Stop end. Body may be removed at any time and another Kuterlite fitting used with the same nut and compression ring

15mm 22mm 28mm



MC63B Blanking discs

15mm 22mm 28mm



MC63C Copper cones

8mm 10mm 15mm 22mm 28mm 3/4" imperial

MC63B Brass cones

8mm 10mm 15mm 22mm 28mm



Manual and Drain Off Radiator Valves

- Suitable for sealed systems (10 bar rated) tested in accordance with BS2767-10
- White handles as standard LS cap included
- Comprehensive range: 10-15mm includes drain off variant
- Chrome plated

Jazz manual radiator valve 15mm



Jazz drain off radiator valve 15mm



Jazz angle radiator valves



Drain off angle radiator

10mm





Push-fit Radiator Valves

- Suitable for PE-X polybutylene, multi-layer pipes (to BS7291: Part 1,2, and 3) and copper pipe (to BS2871: Part 1)
- (NB: Plastic pipes to BS7291 should be used)
- High quality polished chrome finish
- Security clip option to prevent accidental removal of pipe
- 10mm and 15mm straight and elbow adaptors available

Manual radiator valve with straight push-fit 10mm 15mm connections



Manual radiator valve with elbow push-fit connections

10mm



Drain off radiator valves with straight push-fit connections

10mm 15mm



Drain off radiator valves with elbow push-fit



Manual straight radiator valve with push-fit





Servicing Valves, Filling Loop

- Compact design
- Chrome plated
- Quality, durability and economy

M720 straight service valve 15mm x 15mm



M722 straight service valve 15mm x 1/2'



Double check valve - DZR 15mm x 15mm



Filling loop with tee

15mm x 15mm





Thermostatic and Manual Radiator Valves

Thermostatic radiator valve with standard tail 10mm 15mm



TRV and lockshield pack with standard tail



10mm 15mm

Thermostatic radiator valve with self sealing tail



TRV and lockshield pack with self sealing tail



TRV and lockshield pack with drain off



Manual radiator valve with



Manual radiator valve with standard tail



Manual radiator valve with 15mm



Manual radiator valve with standard tail

8mm



Accessories



Self sealing tail



Locking and limiting pin





This certifies that

PEGLER YORKSHIRE GROUP LTD

has had the undermentioned product examined, tested and found, when correctly installed, to comply with the requirements of the United Kingdom Water Supply (Water Fittings) Regulations and Scottish Water Byelaws.

MERCIA 'W' RANGE OF COPPER, DZR BRASS OR GUNMETAL CAPILLARY, LEAD FREE SOLDER RING AND THREADED FITTINGS FOR USE WITH COPPER PIPE

The certificate by itself is not evidence of a valid WRAS Approval. Confirmation of the current status of an approval must be obtained from the WRAS Directory (www.wras.co.uk/directory)

The product so mentioned will be valid until the end of:

October 201



This certifies that

PEGLER YORKSHIRE GROUP LTD

has had the undermentioned product examined, tested and found, when correctly installed, to comply with the requirements of the United Kingdom Water Supply (Water Fittings) Regulations and Scottish Water Byelaws.

MERCIA "E" RANGE OF END FEED FITTINGS FOR USE WITH COPPER PIPE

The certificate by itself is not evidence of a valid WRAS Approval. Confirmation of the current status of an approval must be obtained from the WRAS Directory (www.wras.co.uk/directory)

The product so mentioned will be valid until the end of:

1112116
Certificate No.

K. W. W. Secretary

Chairman, Product Assessment Group

October 2014