

Dry Gauges



All Stainless Steel Dry Gauges, Bottom Connection

Part No.	Type	Case Dia.	Case	Window	Movement	Bourdon Tube	Connection	Entry	Range	Operating Temp.	Accuracy
SSG63-001B	Dry	63MM	Polished s/s 304	Glass	S/S 304	S/S 316	S/S 304	Bottom BSPP 1/4"	0-1 bar /psi	Ambient -20 + 60°C	2.50%
SSG63-004B	Dry	63MM	Polished s/s 305	Glass	S/S 304	S/S 316	S/S 304	Bottom BSPP 1/4"	0-4 bar /psi	Ambient -20 + 60°C	2.50%
SSG63-012B	Dry	63MM	Polished s/s 306	Glass	S/S 304	S/S 316	S/S 304	Bottom BSPP 1/4"	0-12 bar / psi	Ambient -20 + 60°C	2.50%
SSG63-025B	Dry	63MM	Polished s/s 304	Glass	S/S 304	S/S 316	S/S 304	Bottom BSPP 1/4"	0-25 bar / psi	Ambient -20 + 60°C	2.50%
SSG63-060B	Dry	63MM	Polished s/s 308	Glass	S/S 304	S/S 326	S/S 304	Bottom BSPP 1/4"	0-60 bar / psi	Ambient -20 + 60°C	2.50%
SSG63-200B	Dry	63MM	Polished s/s 309	Glass	S/S 304	S/S 316	S/S 304	Bottom BSPP 1/4"	0-200 bar / psi	Ambient -20 + 60°C	2.50%
SSG63-400B	Dry	63MM	Polished s/s 310	Glass	S/S 304	S/S 316	S/S 304	Bottom BSPP 1/4"	0-400 bar / psi	Ambient -20 + 60°C	2.50%

