

Safety Coupling with Push Button 022S.06



Working Temperature:
-20°C up to +100°C (-4°F +212°F)

Flow capacity:
NW-5.5


Working Pressure:
0-12 bar (0-508 PSI)

- Material:**
- Inner part: Aluminium
 - Back part: Brass Nickel Plated
 - Valve: Steel Chrome Plated
 - Spring: Stainless Steel
 - Coupler Body: Steel Chrome Plated
 - Seals: Nitrile (Ni) NBR
 - Balls: AISI 420 Hardened
 - Push Button: AISI 420 Hardened Steel Chrome Plated

- Interchangeability:**
- TST 014 & 022
 - ARO 210
 - Rectus 14 & 22
 - Industrial Interchange 1/4"
 - Orion 44510
 - JWL 522 & 532
 - DynaQuip DM-2
 - Aerequip FD41
 - Gromelle G-16600




Couplers and Plugs	Connection	Order No	SW	L	øD
--------------------	------------	----------	----	---	----




Male Thread Coupling
Kupplung mit Aussengewinde

BSP 1/4"	022.S06 EG 13	20	67.7	25
BSP 3/8"	022.S06 EG 17	20	70.7	25
BSP 1/2"	022.S06 EG 21	24	70.7	25



Female Thread Coupling
Kupplung mit Innengewinde

BSP 1/4"	022.S06 DG 13	20	69.7	25
BSP 3/8"	022.S06 DG 17	20	71.7	25
BSP 1/2"	022.S06 DG 21	24	75.7	25



Standard Hose Barb Coupling
Kupplung mit Schlauchtülle

Ø 6 - 1/4"	022.S06 HG 06	20	84.7	25
Ø 8 - 5/16"	022.S06 HG 08	20	84.7	25
Ø 10 - 3/8"	022.S06 HG 10	20	84.7	25