

# Dry Gauges



## All Stainless Steel Dry Gauges, Bottom Connection

| Part No.   | Type | Case Dia. | Case             | Window        | Movement | Bourdon Tube | Connection | Entry            | Range           | Operating Temp. | Accuracy |
|------------|------|-----------|------------------|---------------|----------|--------------|------------|------------------|-----------------|-----------------|----------|
| SSG63-001B | Dry  | 63MM      | Polished s/s 304 | Polycarbonate | S/S 304  | S/S 316      | S/S 304    | Bottom BSPP 1/4" | 0-1 bar /psi    | -5°C to +60°C   | 2.50%    |
| SSG63-004B | Dry  | 63MM      | Polished s/s 305 | Polycarbonate | S/S 304  | S/S 316      | S/S 304    | Bottom BSPP 1/4" | 0-4 bar /psi    | -5°C to +60°C   | 2.50%    |
| SSG63-012B | Dry  | 63MM      | Polished s/s 306 | Polycarbonate | S/S 304  | S/S 316      | S/S 304    | Bottom BSPP 1/4" | 0-12 bar / psi  | -5°C to +60°C   | 2.50%    |
| SSG63-025B | Dry  | 63MM      | Polished s/s 304 | Polycarbonate | S/S 304  | S/S 316      | S/S 304    | Bottom BSPP 1/4" | 0-25 bar / psi  | -5°C to +60°C   | 2.50%    |
| SSG63-060B | Dry  | 63MM      | Polished s/s 308 | Polycarbonate | S/S 304  | S/S 326      | S/S 304    | Bottom BSPP 1/4" | 0-60 bar / psi  | -5°C to +60°C   | 2.50%    |
| SSG63-200B | Dry  | 63MM      | Polished s/s 309 | Polycarbonate | S/S 304  | S/S 316      | S/S 304    | Bottom BSPP 1/4" | 0-200 bar / psi | -5°C to +60°C   | 2.50%    |
| SSG63-400B | Dry  | 63MM      | Polished s/s 310 | Polycarbonate | S/S 304  | S/S 316      | S/S 304    | Bottom BSPP 1/4" | 0-400 bar / psi | -5°C to +60°C   | 2.50%    |

