

EUROCEL PP 5231

PF52 C/80 BLACK



Description of Product

Film backing: Polyethylene film

Colour: Black

Adhesive Type: Rubber

Technical Data

Thickness: 80µm

Adhesion to stainless steel: 1.3 +/- 0.4 N/cm



Application Conditions

The surface must be free from oil, fat, dust and solvents

Room temperature (> 10C and < 40C)

Resistance

Against moisture: Good

Against oil: Moderate

Against solvents: Moderate

Against UV: 12 months

Storage conditions of rolls

Room temperature (> 10C and < 40C)

Storage time max. 6 months after date of production

No direct exposure to sunlight and moisture

- The low-tack adhesive allows easy unwinding from the roll, avoiding distortion of the film.
- Easy, clean removal from the protected article after use.
- Resistant to moisture, many chemicals, such as diluted acids and alkalis, and salt solutions.
- Suitable for indoors or outdoors.
- Available in all black or black back white surface, can be written on.
- Used as a protection film for the transport of window frames and ladders
- The tape performs well on mild steel, stainless steel and aluminium.

2903/1102 Outdoor Low-Tack Protection Tape, 100 Metre Rolls

Part Number	mm	Colour
2903BLACKBLACK50	50	Black/Black
2903BLACKBLACK75	75	Black/Black