



37-4170 - (2405)

JIC Male 37 Deg Cone x NPT Female Extended



BRENNAN INDUSTRIES, EXTRAORDINARY FITTINGS

In business for over 60 years, Brennan supplies more than 50,000 types of hydraulic fittings and adaptors in sizes ranging from 1/16 to 3 inches.


Learn More at Brennan University:

[Fittings 101](#)

[Tube Fittings Resources](#)

[Literature and Certifications](#)

Tech Data Sheet: 71389



37-4170 - (2405)

DESCRIPTION:

JIC MALE 37 DEG CONE X NPT FEMALE
EXTENDED

UK PART NUMBER:

37-4170

US PART NUMBER:

2405

Item	TUBE O.D.	B1 SAE 37 Deg	A2 NPTF	B1 DRILL	L LGTH	C HEX	Material
37-4170-02-02	1/8	5/16-24	1/8-27	0.062	1.120	0.562	STEEL
37-4170-02-04	1/8	5/16-24	1/4-18	0.083	1.290	0.750	STEEL
37-4170-03-02	3/16	3/8-24	1/8-27	0.125	1.130	0.562	STEEL
37-4170-03-04	3/16	3/8-24	1/4-18	0.125	1.310	0.750	STEEL
37-4170-04-02	1/4	7/16-20	1/8-27	0.172	1.19	0.562	STEEL
37-4170-04-04	1/4	7/16-20	1/4-18	0.172	1.390	0.750	STEEL
37-4170-04-06	1/4	7/16-20	3/8-18	0.172	1.450	0.875	STEEL
37-4170-04-08	1/4	7/16-20	1/2-14	0.172	1.68	1.125	STEEL
37-4170-05-02	5/16	1/2-20	1/8-27	0.234	1.170	0.562	STEEL
37-4170-05-04	5/16	1/2-20	1/4-18	0.234	1.390	0.750	STEEL
37-4170-05-06	5/16	1/2-20	3/8-18	0.234	1.450	0.875	STEEL
37-4170-05-08	5/16	1/2-20	1/2-14	0.234	1.680	1.125	STEEL
37-4170-06-02	3/8	9/16-18	1/8-27	0.297	1.190	0.625	STEEL
37-4170-06-04	3/8	9/16-18	1/4-18	0.297	1.40	0.750	STEEL
37-4170-06-06	3/8	9/16-18	3/8-18	0.297	1.46	0.875	STEEL
37-4170-06-08	3/8	9/16-18	1/2-14	0.297	1.690	1.125	STEEL
37-4170-06-12	3/8	9/16-18	3/4-14	0.297	1.75	1.375	STEEL
37-4170-08-04	1/2	3/4-16	1/4-18	0.391	1.550	0.813	STEEL
37-4170-08-06	1/2	3/4-16	3/8-18	0.391	1.560	0.875	STEEL
37-4170-08-08	1/2	3/4-16	1/2-14	0.391	1.79	1.125	STEEL
37-4170-08-12	1/2	3/4-16	3/4-14	0.391	1.850	1.375	STEEL
37-4170-08-16	1/2	3/4-16	1-11 1/2	0.391	2.100	1.625	STEEL
37-4170-10-04	5/8	7/8-14	1/4-18	0.484	1.660	0.938	STEEL
37-4170-10-06	5/8	7/8-14	3/8-18	0.484	1.670	0.938	STEEL
37-4170-10-08	5/8	7/8-14	1/2-14	0.484	1.89	1.125	STEEL
37-4170-10-12	5/8	7/8-14	3/4-14	0.484	1.95	1.375	STEEL
37-4170-10-16	5/8	7/8-14	1-11 1/2	0.484	2.20	1.625	STEEL
37-4170-12-08	3/4	1 1/16-12	1/2-14	0.609	2.05	1.125	STEEL
37-4170-12-12	3/4	1 1/16-12	3/4-14	0.609	2.06	1.375	STEEL
37-4170-12-16	3/4	1 1/16-12	1-11 1/2	0.609	2.30	1.625	STEEL
37-4170-14-08	7/8	1 3/16-12	1/2-14	0.719	2.05	1.375	STEEL
37-4170-14-12	7/8	1 3/16-12	3/4-14	0.719	2.06	1.375	STEEL
37-4170-16-12	1	1-5/16-12	3/4-14	0.844	2.110	1.375	STEEL
37-4170-16-16	1	1 5/16-12	1-11 1/2	0.844	2.350	1.625	STEEL
37-4170-16-20	1	1-5/16-12	1-1/4-11 1/2	0.844	2.440	2.000	STEEL
37-4170-20-16	1 1/4	1 5/8-12	1-11 1/2	1.078	2.47	1.687	STEEL
37-4170-20-20	1 1/4	1 5/8-12	1 1/4-11 1/2	1.078	2.49	2.000	STEEL
37-4170-20-24	1 1/4	1 5/8-12	1 1/2-11 1/2	1.078	2.500	2.375	STEEL
37-4170-24-20	1-1/2	1-7/8-12	1-1/4-11 1/2	1.312	2.590	2.000	STEEL
37-4170-24-24	1 1/2	1 7/8-12	1 1/2-11 1/2	1.312	2.62	2.375	STEEL
37-4170-24-32	1 1/2	1 7/8-12	2-11 1/2	1.312	2.72	2.875	STEEL
37-4170-32-24	2	2 1/2-12	1 1/2-11 1/2	1.781	2.950	2.625	STEEL
37-4170-32-32	2	2 1/2-12	2-11 1/2	1.781	2.97	2.875	STEEL
37-4170-40-40	2-1/2	3-12	2-1/2-8	2.318	2.780	3.250	STEEL