

## FEATURES



Anti-Static



Fiberglass Toecap



PS Rated Penetration Resistant Insert



Ladder Grip



Non Metallic



Ankle Protection



Fuel Oil Resistant Outsole



Heat Resistant Outsole to 300C



Water Repellent Upper



Fully Waterproof

## INDUSTRIES



Agricultural



Airsides



Construction



Emergency Services



Highways



House builders



Offshore



Quarry and Mining



Rail



Security

## Product Details

Colour: Black  
Size Range: UK 3-13  
Height: 8.5 inches  
Weight: 953g



## PRODUCT DESCRIPTION

RF605 Challenger Unrivaled protection meets supreme comfort. Featuring BOA® Fit System for precision fit, premium water-repellent full-grain leather, fiberglass toecap, and waterproof construction. Activ-Step® anti-penetration insert and Cushion Pro footbed offer ultimate safety and support. Rugged outsole with scuff cap ensures superior traction in challenging terrains.

## MATERIAL BREAKDOWN

**UPPER MATERIAL:** Leather Working Group Certified, Water Repellent Full Grain Leather  
**EYELETS:** BOA® Eyestay Guard  
**LACES:** BOA® Fit System  
**FOOTBED:** Activ-Step® PU Foam, 100% Post Consumer Recycled Polyester Top Mesh  
**LINING:** Waterproof Construction, 40% Nylon, 60% Post Consumer Recycled Polyester  
**OUTSOLE:** PU Midsole, Nitrile Rubber  
**PROTECTIVE TOECAP:** Fiberglass  
**PROTECTIVE MIDSOLE:** Activ-Step® PS Rated Penetration Resistant Insert

## TECHNOLOGIES & ACCREDITATIONS



Category	SB	S1	S2	S3/L/S	S4	S5/L/S	S6	S7/L/S
Class 1	✓	✓	✓	✓	✗	✗	✓	✓
Class 2	✗	✗	✗	✗	✓	✓	✗	✗
200 Joules Toecap	✓	✓	✓	✓	✓	✓	✓	✓
Closed heel Area	✗	✓	✓	✓	✓	✓	✓	✓
Energy Absorption Of Seat Region	✗	✓	✓	✓	✓	✓	✓	✓
Anti-Static	✗	✓	✓	✓	✓	✓	✓	✓
Water Penetration And Absorption	✗	✗	✓	✓	✗	✗	✓	✓
Perforation Resistance To The Type	✗	✗	✗	✓	✗	✓	✗	✓
Cleated Outside	✗	✗	✗	✓	✗	✓	✗	✓
Water Resistance Of The Entire Shoe	✗	✗	✗	✗	✗	✗	✓	✓

### EN 2022 SPECIFICATION

Safety footwear is classified in the UK and EU by the EN 20345 standard using a categorisation of S1 through to S7 to quickly determine the level of incorporated safety components. This is further supported by letter codes for additional safety components or tests the footwear has undergone.

For further information contact the Rock Fall sales team.

Always check with your health and safety management if you are unsure of the appropriate specification required by your workplace.

**Class 1** refers to footwear made from leather & other materials, excluding all polymeric and all rubber footwear  
**Class 2** Refers to all polymeric footwear including all rubber footwear.

**S3, S5, S7** Specify metallic midsole tested at 1100N.

**S3L, S5L, S7L** specify non-metal midsole tested at 1100N with a 4.5mm nail.

**S3S, S5S, S7S** specify non-metal midsole tested at 1100N with a 3mm nail.

Please note that the EN20345:2022 specification does not necessarily apply to the footwear represented here, and that there are further specifications attaining to specific safety tests and standards. Always check specification and standards of the footwear before purchase. For more information on specifications and standards, get in touch with our team for complete guide.

## WELLBEING & COMFORT

When you spend your working day on your feet, discomfort and incorrect footwear can cause serious long-term issues. That's why our footwear is designed to support your feet where they need it most, and we have a wide variety of styles to fit every kind of foot. Make sure your footwear is providing the correct arch support, and that your footwear is the correct size for your feet.

## FOOTWEAR CARE

Keeping your safety footwear in a good condition helps keep them comfortable and extend their useful life. Always make sure to keep the upper and sole clear of extensive mud or residue, using a brush and warm water to clean. Never dry out footwear using heat (such as placing them near a radiator) always allow them to dry naturally. Use a leather nourishment or dubbin wax to keep leather materials from drying out.



Danmark

# EU-Type Examination Certificate

No. DK-PPE002239 i01

**Holder of Certificate:** **ROCK FALL UK LTD**  
Major House, Wimsey Way, Alfreton Trading Estate  
Alfreton, Derbyshire DE55 4LS  
UNITED KINGDOM

**Product:** **Safety Footwear**  
**Model(s):** **RF605 Challenger BOA Safety Boot**

**Tested according to:** EN ISO 20345:2022+A1:2024

**Parameters:**

Category:	II
Class of Protection:	S7S AN CI HI HRO LG SC FO SR
Size Range:	35-51
Toecap:	3160 Fiber Glass Toecap
Insert:	Aramid Fibre
Outsole:	3160 PU/RB
Construction:	Injection

The Certification Body of TÜV SÜD DANMARK ApS confirms that the listed product fulfils the applicable essential health and safety requirements with Annex V (Module B) of Regulation (EU) 2016/425 on personal protective equipment according to Article 19 (PPE of category II).  
For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Evaluation report no.:** DK-PPE002239 TRF i01  
**Valid until:** 2031-03-16  
**Date,** 2026-03-17

( Jamie Zhang )

Page 1 of 1

This certificate has been issued in accordance with the TÜV SÜD Testing, Certification, Validation and Verification Regulations and constitutes the main page(s) of the combined Certificate and Annex. The Conditions for the validity of this certificate are listed in the Annex.  
For further details, related to this certification please contact [babt@tuvsud.com](mailto:babt@tuvsud.com)

TÜV SÜD DANMARK ApS is Notified Body according to Regulation (EU) 2016/425 on personal protective equipment with the identification number 2443.

TÜV SÜD DANMARK ApS • Johanne Møllers Passage 1, 3. sal • 1799 Copenhagen V • Denmark

## EU DECLARATION OF CONFORMITY

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM**

Declares that the PPE described hereafter;

### **ROCK FALL RF605 Challenger**

Is in conformity with the provisions of PPE Regulation EU 2016/425 for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345:2022+A1:2024**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM**

Is identical to the PPE submitted to: **TUV SUD DANMARK ApS, Johanne Mollers Passage 1, 3, 1799 Copenhagen V Danmark. Notified Body 2443** who performed the Eu type examination (Module B) and issued the EU type examination certificate: **DK-PPE002239 i01**

The PPE is subject to the procedure set out in **Module C** of the PPE Regulation EU 2016/425 under the supervision of the notified body: **TUV SUD DANMARK ApS, Johanne Mollers Passage 1, 3, 1799 Copenhagen V Denmark. Notified Body 2443.**

Signature:

A handwritten signature in black ink, appearing to read "R. K. Wilson".

Position: Director

Date: 17/03/2026

## Certificate of Conformance

Issued To : ROCK FALL UK

Our Reference No.: GZHT9139108402

Certificate Issue Date: Feb 05, 2026

Buyer's Name --  
Ref. No. RF605  
Brand --  
Manufacturer --

We hereby declare that the product category (group) above has been tested by Intertek and meets the requirements of ASTM Specification ASTM F2413-24 as tested in accordance with ASTM Test Methods F2412-24 list the safety hazard(s) tested below.

Tests List:

Protective Toe Impact Resistance (I)  
Protective Toe Compression Resistance (C)  
Puncture Resistance Footwear (PR)

The test results are given in our report No. GZHT91391084, date Feb 05, 2026

Note:

1. This declaration applies to the particular sample tested and to the specific tests carried out as dated and detailed in the report(s) referenced above.

---

Approved By:

Intertek Testing Services Shenzhen  
Limited, Guangzhou Branch



Guiliang Dong  
Senior Lab Manager

**Intertek Testing Services Shenzhen Limited, Guangzhou Branch**

Page 1/1

Room 401/501/601/701-1/801/901/1003, No. 8, East BaoYing Road  
Huangpu District, Guangzhou 510730

深圳天祥质量技术服务有限公司广州分公司

广州市黄埔区保盈东路8号401房、501房、601房、701房-1、801房、901房、1003房  
Tel: +86 020-28209114 Postcode:510730

www.intertek.com