Rock Fall®
INDUSTRY DEFINING SAFETY FOOTWEAR

Style Ref.
RF328

Style Name.
Chatsworth

Specification: EN ISO 20345:2022 SB CI E HRO PS WPA WR FO SR + ASTM F2413-24I/C EH PR + BS EN 17249:2013 + AS 2210:3:2019 SB CI E HRO P WRU WR FO SRC

FEATURES

- Class 3 Chainsaw
- Climbing Iron Compatible
- Electrical Hazard
- Fibreglass Toecap
- PS Rated Penetration Resistant Insert
- Ladder Grip
- Cold Insulation
- Fuel Oil Resistant Outsole
- Heat Resistant Outsole to 300c
- Water Repellent Upper

INDUSTRIES

- Agricultural
- Construction
- Electric Vehicle
- Rail
- Utilities

Product Details

Colour: Black
Size Range: UK 6 - 13 (INC 6.5)
Height: 8.5 inches
Weight: 1283g

PRODUCT DESCRIPTION

RF328 Chatsworth Class 3 Chainsaw Safety Boot, certified to withstand chain speeds of 63MPH under BS EN 17249:2013 and tested to 20kV AC Electrical Hazard protection. Featuring FORCE10® dual density outsole, Moisture Tech waterproofing, steel toe cap and chainsaw kickback shield for uncompromising professional protection.

MATERIAL BREAKDOWN

UPPER MATERIAL: Leather Working Group Certified, Water Repellent Full Grain Leather
EYELETS: Plastic
LACES: 100% Post Consumer Recycled Polyester
FOOTBED: Activ-Step® PU Foam, 100% Post Consumer Recycled Polyester Top Mesh
LINING: 60% Post Consumer Recycled Polyester, 40% Nylon, Activ-Step® Aramid Fibre Chainshaw Snagging Insert
SCUFF CAP: FORCE10® 59% Bio TPU
OUTSOLE: FORCE10® Dual Density PU, Nitrile Rubber
DIGGING PLATE: Impact Shield™ Polypropylene
PROTECTIVE TOECAP: Steel
PROTECTIVE MIDSOLE: Activ-Step® PS Rated Penetration Resistant Insert

TECHNOLOGIES & ACCREDITATIONS

FORCE10®
FSC www.fsc.org FSC® C162556
HELCOR® LEDER-TEC
IMPACT SHIELD INTERNAL DIGGING PLATE
PRINTED WITH SOY INK®
RTEN™ ABRASION RESISTANT THREAD

More info on this style at:
WWW.ROCKFALL.COM/PRODUCTS/CHATSWORTH

Tel. +44 (0) 1773 608616
Email. sales@rockfall.com

Rock Fall UK
Wimsey Way, Somercoates
Alfreton DE55 4LS
United Kingdom

Rock Fall®
INDUSTRY DEFINING SAFETY FOOTWEAR

OVERVIEW OF SAFETY STANDARDS

Category	SB	S1	S2	S3/L/S	S4	S5/L/S	S6	S7/L/S
Class 1	✔	✔	✔	✔	✕	✕	✔	✔
Class 1	✕	✕	✕	✕	✔	✔	✕	✕
200 Joules Toecap	✔	✔	✔	✔	✔	✔	✔	✔
Closed heel Area	✕	✔	✔	✔	✔	✔	✔	✔
Energy Absorption Of Seat Region	✕	✔	✔	✔	✔	✔	✔	✔
Anti-Static	✕	✔	✔	✔	✔	✔	✔	✔
Water Penetration And Absorption	✕	✕	✔	✔	✕	✕	✔	✔
Perforation Reistance To The Type	✕	✕	✕	✔	✕	✔	✕	✔
Cleated Outside	✕	✕	✕	✔	✕	✔	✕	✔
Water Resistance Of The Entire Shoe	✕	✕	✕	✕	✕	✕	✔	✔

EN 2022 SPECIFICATION

Safety footwear is classified in the UK and EU by the EN 20345 standard using a categorisation of S1 through to S7 to quickly determine the level of incorporated safety components. This is further supported by letter codes for additional safety components or tests the footwear has undercone.

For further infomation contact the Rock Fall sales team.

Always check with your health and safety managment if you are unsure of the appropriate specification required by your workplace.

Class 1 refers to footwear made from leather & other materials, excluding all polymeric and all rubber footwear
Class 2 Refers to all polymetric footwear including all rubber footwear.

S3, S5, S7 Specify metallic midsole tessted at 1100N.
S3L, S5L, S7L specifiy non-metal midsole tested at 1100N with a 4.5mm nail.
S3S, S55, S75 specifiy non-metal midsole tested at 1100N with a 3mm nail.

Please note that the EN20345:2022 specification does not necessarily apply to the footwear represented here, and that there are further specifications attaining to specific safety tests and standards. Always check specification and standards of the footwear before purchase. For more infomation on specifications and standards, get in touch with our team for complete guide.

WELLBEING & COMFORT

When you spend your working day on your feet, discomfort and incorrect footwear can cause serious long-term issues. That's why our footwear is designed to support your feet where they need it most, and we have a wide variety of styles to fit every kind of foot. Make sure your footbed is providing the correct arch support, and that your footwear is the correct size for your feet.

FOOTWEAR CARE

Keeping your safety footwear in a good condition helps keep them comfortable and extend their useful life. Always make sure to keep the upper and sole clear of extensive mud or residue, using a brush and warm water to clean. Never dry out footwear using heat (such as placing them near a radiator) always allow them to dry naturally. Use a leather nourishment or dubbin wax to keep leather materials from drying out.

PRODUCT DISCLAIMER

This footwear is Electrical Hazard and tested in accordance with the test method as set out within ASTM F2412-24. This protection deteriorates rapidly in humid, damp and wet environments and with wear. Electrical Hazard (EH) Safety footwear is intended as secondary source protection equipment and not for live working.

More info on this style at:

WWW.ROCKFALL.COM/PRODUCTS/CHATSWORTH

Tel. +44 (0) 1773 608616
Email. sales@rockfall.com

Rock Fall UK
Wimsey Way, Somercoates
Alfreton DE55 4LS
United Kingdom

Issued to:

Rock Fall UK Ltd
Major House
Unit 1/3 Wimsey Way
Alfreton
Derbyshire
DE55 4LS
UK

Notified Body: 2777

SATRA customer number: P1769

EU Type-Examination Certificate

Certificate number: 2777/11346-03/E00-00

This EU Type-Examination Certificate covers the following product group(s) supported by testing to the relevant standards/technical specifications and examination of the technical file documentation. It has been issued Under Module B of Regulation 2016/425 on personal protective equipment. This product group has been shown to satisfy the applicable essential health and safety requirements as a Category III product.

Product reference:	**Description:**
RF 328 Chatsworth	Height of upper: Half-knee Upper 1: 2.2-2.4mm black full grain leather Upper 2: 2.0mm black helcor leather Upper 3: 1.6mm Black leather Vamp lining/Quarter lining/counter lining: Grey Sympatex lining with 14 layers cut resistance white linings Collar/Tongue lining: Black sandwich mesh Collar: 1.6mm yellow/green leather Tongue: 1.6mm black leather Fastening: 7 pairs of plastic loops Toe-cap: PEP-Steel toecap Perforation resistance insert/Insole: Composite non-metallic insert plate Construction: Cemented Insock: Green mesh + PU full removeable insock Sole: PU/Rubber sole Sole Pattern: GR360 FORCE 10 Size Range: 38-48 European

Classification:

EN 17249:2013 – Class 3

EN ISO 20345:2022 – SB PS CI E WPA WR SC HRO FO SR

ASTM F2413-18- M/I/C EH PR

AS/NZ 2210.3:2009- SB P CI E FO WRU WR SRC

Standards/Technical specifications applied:
EN ISO 17249:2013

Technical reports/Approval documents:
SATRA: FWT0293691 2002, CHT0348196/2315, CHT0350470/2322, CHT0336968/2235/A, CHT2137P7K4
Intertek: GZHT90737593, GZHT90747524, GZHT90544038, GZHT91168397
CTC: 171223899, 180303795, 480713450,180610768_1

Signed on behalf of SATRA: Geoff Graham

Date first issued: 11/10/2018
Date of issue: 12/09/2023
Expiry date: 12/09/2028

Rock Fall UK, Major House,
Unit 1/3, Wimsey Way,
Alfreton, Derbyshire, DE55 4LS
United Kingdom
Tel: **01773 608616**
Email: **sales@rockfall.com**
rockfall.com

EU DECLARATION OF CONFORMITY

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Declares that the PPE described hereafter;

ROCK FALL RF328 Chatsworth
Is in conformity with the provisions of PPE Regulation EU 2016/425 for **Category III** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345+A1:2024; EN ISO17249:2013**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Is identical to the PPE submitted to: **SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, D15YN2P, Republic of Ireland. Notified Body 2777.** who performed the Eu type examination (Module B) and issued the EU type -examination certificate: **2777/11346-03/E00-00**

The PPE is subject to the procedure set out in **Module C2** of the PPE Regulation EU 2016/425 under the supervision of the notified body:

SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, D15YN2P, Republic of Ireland. Notified Body 2777

Signature: Position: Director Date: 12/09/2023

Certificate of Conformance (COC)

Certificate No. 2412009

Issued by CTC Dongguan Co., Ltd., to the following model of PPE footwear:

Company name: ROCK FALL UK LTD

Product Description: OUTSOLE: 2171#, TOECAP: PEP-STEEL, INSERT: PEP-COMPOSITE
Style name: RF328
Gender: Male

Picture of footwear & outsole	Picture of non-metal puncture resistance insert

This product meets the performance requirements of ASTM Specification F2413-24 as tested in accordance with ASTM Test Methods F2412-24 for the following safety hazards:

Safety hazards	CTC testing report No.	Issued date of report
5.2 Impact Resistant (I)	D241234944_1	17 December, 2024
5.3 Compression Resistant (C)	D241234944_1	17 December, 2024
5.6 Electrical Hazard Resistant Footwear (EH)	D241234944_1	17 December, 2024
5.8 Puncture Resistant (PR) 5.8.7 Determination of puncture force 5.8.8 Determination of the flex resistance of puncture-resistant insert	D241236354_1	30 December, 2024

Note :
1. This declaration applies to the particular sample tested and to the specific tests carried out as dated and detailed in the report(s) referenced above.
2. This certificate is valid only for the applicant's selected test items and must not be used without the attached test report(s).

Issue date of certificate:
December 31, 2024

Issued in Dongguan by:
Kevin LEE
PPE Manager of CTC Greater China

CTC Dongguan Co., Ltd.
1 Floor, No.14 building, Small and Medium sized Enterprises Pioneer Park,
SSL Industry Park, Dongguan - P.R. CHINA
Tél. : +86 769 23 03 77 70 Fax : +86 769 23 03 77 71
E-mail : ctcdongguan@ctcgroupe.com