

FEATURES



Anti-Static



Fiberglass Toecap



PS Rated Penetration Resistant Insert



Internal Metatarsal Guard



Ladder Grip



Non Metallic



Fuel Oil Resistant Outsole



Heat Insulation



Heat Resistant Outsole to 300c



Water Repellent Upper

INDUSTRIES



Construction



Highways



Offshore



Quarry and Mining



Rail



Utilities

Product Details

Colour: Black
Size Range: UK 5-15
Height: 9.5 inches
Weight: 1183g



PRODUCT DESCRIPTION

RF710 Magma Cutting-edge safety boot engineered for extreme work environments. Premium water-resistant leather, Activ-Step® fibreglass toecap, penetration-resistant midsole, and IMPACTSHIELD™ metatarsal guard offer unparalleled protection. BOA® Fit System ensures precision fit, while FORCE10® outsole provides superior traction and heat resistance.

MATERIAL BREAKDOWN

UPPER MATERIAL: Water Repellent Full Grain Leather, LWG Certified
EYELETS: BOA® Eyestay Guard
LACES: BOA® Fit System
FOOTBED: Activ-Step® PU Foam, 100% Post Consumer Recycled Polyester Top Mesh
LINING: Waterproof Construction, 40% Nylon, 60% Post Consumer Recycled Polyester
SCUFF CAP: FORCE10® TPU
KICK PROTECTOR: TPU
OUTSOLE: FORCE10® Nitrile Rubber
DIGGING PLATE: Impact Shield™ Polypropylene
PROTECTIVE TOECAP: Fibreglass
PROTECTIVE MIDSOLE: Activ-step® PS Rated Penetration Resistant Insert
PROTECTIVE METATARSAL GUARD: Impact Shield™ - PU Foam & Rubber

TECHNOLOGIES & ACCREDITATIONS



Category	SB	S1	S2	S3/L/S	S4	S5/L/S	S6	S7/L/S
Class 1	✓	✓	✓	✓	✗	✗	✓	✓
Class 2	✗	✗	✗	✗	✓	✓	✗	✗
200 Joules Toecap	✓	✓	✓	✓	✓	✓	✓	✓
Closed heel Area	✗	✓	✓	✓	✓	✓	✓	✓
Energy Absorption Of Seat Region	✗	✓	✓	✓	✓	✓	✓	✓
Anti-Static	✗	✓	✓	✓	✓	✓	✓	✓
Water Penetration And Absorption	✗	✗	✓	✓	✗	✗	✓	✓
Perforation Resistance To The Type	✗	✗	✗	✓	✗	✓	✗	✓
Cleated Outside	✗	✗	✗	✓	✗	✓	✗	✓
Water Resistance Of The Entire Shoe	✗	✗	✗	✗	✗	✗	✓	✓

EN 2022 SPECIFICATION

Safety footwear is classified in the UK and EU by the EN 20345 standard using a categorisation of S1 through to S7 to quickly determine the level of incorporated safety components. This is further supported by letter codes for additional safety components or tests the footwear has undergone.

For further information contact the Rock Fall sales team.

Always check with your health and safety management if you are unsure of the appropriate specification required by your workplace.

Class 1 refers to footwear made from leather & other materials, excluding all polymeric and all rubber footwear
Class 2 Refers to all polymeric footwear including all rubber footwear.

S3, S5, S7 Specify metallic midsole tested at 1100N.

S3L, S5L, S7L specify non-metal midsole tested at 1100N with a 4.5mm nail.

S3S, S5S, S7S specify non-metal midsole tested at 1100N with a 3mm nail.

Please note that the EN20345:2022 specification does not necessarily apply to the footwear represented here, and that there are further specifications attaining to specific safety tests and standards. Always check specification and standards of the footwear before purchase. For more information on specifications and standards, get in touch with our team for complete guide.

WELLBEING & COMFORT

When you spend your working day on your feet, discomfort and incorrect footwear can cause serious long-term issues. That's why our footwear is designed to support your feet where they need it most, and we have a wide variety of styles to fit every kind of foot. Make sure your footwear is providing the correct arch support, and that your footwear is the correct size for your feet.

FOOTWEAR CARE

Keeping your safety footwear in a good condition helps keep them comfortable and extend their useful life. Always make sure to keep the upper and sole clear of extensive mud or residue, using a brush and warm water to clean. Never dry out footwear using heat (such as placing them near a radiator) always allow them to dry naturally. Use a leather nourishment or dubbin wax to keep leather materials from drying out.



Issued to:

Rock Fall UK Ltd
Major House
Unit 1/3 Wimsey Way
Alfreton
Derbyshire
DE55 4LS
United Kingdom

Notified Body: 2777

SATRA customer number: P1769

EU Type-Examination Certificate

Certificate number: 2777/15568-02/E00-00

This EU Type-Examination Certificate covers the following product group(s) supported by testing to the relevant standards/technical specifications and examination of the technical file documentation. It has been issued Under Module B of Regulation 2016/425 on personal protective equipment. This product group has been shown to satisfy the applicable essential health and safety requirements as a Category II product.

Product reference:

Rock Fall RF709 LAVA

Rock Fall RF710 MAGMA

Description:

Height of upper: Ankle boot (RF709) / Half-knee boot (RF710)
Upper: 1.8-2.0mm black full grain leather
Vamp/quarter/counter lining: Grey sympatex
Collar/tongue lining: Black sandwich mesh
Collar/tongue: Black PU
Fastening: BOA® fastening system
Toe-cap: PEP-composite toe cap
Perforation resistance insert / insole: White composite insert plate
Metatarsal protector: Black rubber + blue PU foam
Construction: Cemented
Insock: Green mesh with green PU
Sole: Black rubber outsole
Sole Pattern: 2147#

Sizes: UK 3-16

Classification:

EN ISO 20345:2022 S7S HI CI M SC HRO FO SR

Standards/Technical specifications applied:
EN ISO 20345:2022

Technical reports/Approval documents:

SATRA: CHT0288579/1932, CHT0289394/1936, CHT0295327/2008, CHT0295328/2008, CHT0302306/2037/Issue 3, CHT0293351/1951, CHT0336968/2235/A, CHT2137P7K4, CHT1540T4J8, CHT0348196/2315, CHT2005238 2419 1 CTC: D171223899_1, D200403963_1, D221022386_1, D221022388_2, D230406764_1, Intertek: GZHT90965347, GZHT90980551, GZHT90989386, GZHT90737593, GZHT91008322, GZHT90980549, GZHT90970753, GZHT91148023, CTT: CTT2403014736EN, CTT2403014737EN

Signed on behalf of SATRA:

Geoff Graham

Date first issued: 08/01/2021

Date of issue: 13/06/2024

Expiry date: 13/06/2029



EU DECLARATION OF CONFORMITY

Rock Fall UK, Major House,
Unit 1/3, Wimsey Way,
Alfreton, Derbyshire, DE55 4LS
United Kingdom
Tel: **01773 608616**
Email: **sales@rockfall.com**
rockfall.com

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Declares that the PPE described hereafter;

ROCK FALL RF710 Magma

Is in conformity with the provisions of PPE Regulation EU 2016/425 for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO20345:2022**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Is identical to the PPE submitted to: **SATRA technology Europe Ltd, Bracetown Business Park, Clonee, D15Y N2P, Republic of Ireland. Notified body 2777** who performed the Eu type examination (Module B) and issued the EU type -examination certificate: **2777/15568-02/E00-00**

The PPE is subject to the procedure set out in **Module C** of the PPE Regulation EU 2016/425 under the supervision of the notified body:

SATRA technology Europe Ltd, Bracetown Business Park, Clonee, D15Y N2P, Republic of Ireland. Notified Body 2777

Signature:

Position: Director

Date: 13/06/2024


Certificate of Conformance (COC)

Certificate No. 2504082

Issued by CTC Dongguan Co., Ltd., to the following model of PPE footwear:

Company name: ROCK FALL UK LTD

Product Description: OUTSOLE: 2147#, TOECAP: PEP-COMPOSITE, MIDSOLE: PEP-COMPOSITE
 Style name: RF710 / Gender: Unisex (Tested size US9)



This product meets the performance requirements of ASTM Specification F2413-24 as tested in accordance with ASTM Test Methods F2412-24 for the following safety hazards:

Safety hazards	CTC testing report No.	Issued date of report
5.2 Impact Resistant (I)	D250306969_3	29 April, 2025
5.3 Compression Resistant (C)	D250306969_3	29 April, 2025
5.4 Metatarsal protection (Mt)	D250306969_3	29 April, 2025
5.7 Static dissipative footwear (SD) - SD 100	D250306969_3	29 April, 2025
5.8 Puncture Resistant (PR) 5.8.7 Determination of puncture force 5.8.8 Determination of the flex resistance of puncture-resistant insert	D241236354_1	30 December, 2024

Note :

1. This declaration applies to the particular sample tested and to the specific tests carried out as dated and detailed in the report(s) referenced above.
2. This certificate is valid only for the applicant's selected test items and must not be used without the attached test report(s).

Issue date of certificate:
April 30, 2025

Issued in Dongguan by:
Kevin LEE
PPE Manager of CTC Greater China



CTC Dongguan Co., Ltd.

1 Floor, No.14 building, Small and Medium sized Enterprises Pioneer Park,
 SSL Industry Park, Dongguan - P.R. CHINA
 Tél. : +86 769 23 03 77 70 Fax : +86 769 23 03 77 71
 E-mail : ctcdongguan@ctcgroupe.com