

FEATURES



Anti-Static



Fibreglass Toecap



PS Rated Penetration Resistant Protective Midsole



Ladder Grip



Ankle Protection



Fuel Oil Resistant Outsole



Heat Resistant Outsole to 300c



Water Repellent Upper



Fully Waterproof



Recycled Materials

INDUSTRIES



Agricultural



Airsides



Construction



Emergency Services



Highways



House builders



Offshore



Quarry and Mining



Rail



Security

Product Details

Colour: Black
Size Range: UK 3-13
Height: 8.5 inches
Weight: 944g



PRODUCT DESCRIPTION

RF605 Challenger: Unrivalled protection meets supreme comfort. Featuring BOA® Fit System for precision adjustment, premium water-repellent leather, fibreglass toecap, and Activ-Step® anti-perforation insert. Waterproof construction and rugged outsole ensure optimal performance in challenging conditions.

MATERIAL BREAKDOWN

UPPER MATERIAL: Water Repellent Full Grain Leather, LWG Certified
EYELETS: BOA® Eyestay Guard
LACES: BOA® Fit System
FOOTBED: Activ-Step® PU Foam, 100% Post Consumer Recycled Polyester Top Mesh
LINING: Waterproof Construction, 40% Nylon, 60% Post Consumer Recycled Polyester
OUTSOLE: PU Midsole, Nitrile Rubber
PROTECTIVE TOECAP: Fibreglass
PROTECTIVE MIDSOLE: Activ-step® PS Rated Penetration Resistant Insert

TECHNOLOGIES & ACCREDITATIONS



Category	SB	S1	S2	S3/L/S	S4	S5/L/S	S6	S7/L/S
Class 1	✓	✓	✓	✓	✗	✗	✓	✓
Class 2	✗	✗	✗	✗	✓	✓	✗	✗
200 Joules Toecap	✓	✓	✓	✓	✓	✓	✓	✓
Closed heel Area	✗	✓	✓	✓	✓	✓	✓	✓
Energy Absorption Of Seat Region	✗	✓	✓	✓	✓	✓	✓	✓
Anti-Static	✗	✓	✓	✓	✓	✓	✓	✓
Water Penetration And Absorption	✗	✗	✓	✓	✗	✗	✓	✓
Perforation Resistance To The Type	✗	✗	✗	✓	✗	✓	✗	✓
Cleated Outside	✗	✗	✗	✓	✗	✓	✗	✓
Water Resistance Of The Entire Shoe	✗	✗	✗	✗	✗	✗	✓	✓

EN 2022 SPECIFICATION

Safety footwear is classified in the UK and EU by the EN 20345 standard using a categorisation of S1 through to S7 to quickly determine the level of incorporated safety components. This is further supported by letter codes for additional safety components or tests the footwear has undergone.

For further information contact the Rock Fall sales team.

Always check with your health and safety management if you are unsure of the appropriate specification required by your workplace.

Class 1 refers to footwear made from leather & other materials, excluding all polymeric and all rubber footwear
Class 2 Refers to all polymeric footwear including all rubber footwear.

S3, S5, S7 Specify metallic midsole tested at 1100N.

S3L, S5L, S7L specify non-metal midsole tested at 1100N with a 4.5mm nail.

S3S, S5S, S7S specify non-metal midsole tested at 1100N with a 3mm nail.

Please note that the EN20345:2022 specification does not necessarily apply to the footwear represented here, and that there are further specifications attaining to specific safety tests and standards. Always check specification and standards of the footwear before purchase. For more information on specifications and standards, get in touch with our team for complete guide.

WELLBEING & COMFORT

When you spend your working day on your feet, discomfort and incorrect footwear can cause serious long-term issues. That's why our footwear is designed to support your feet where they need it most, and we have a wide variety of styles to fit every kind of foot. Make sure your footwear is providing the correct arch support, and that your footwear is the correct size for your feet.

FOOTWEAR CARE

Keeping your safety footwear in a good condition helps keep them comfortable and extend their useful life. Always make sure to keep the upper and sole clear of extensive mud or residue, using a brush and warm water to clean. Never dry out footwear using heat (such as placing them near a radiator) always allow them to dry naturally. Use a leather nourishment or dubbin wax to keep leather materials from drying out.

Certificate of Conformance

Issued To : ROCK FALL UK

Our Reference No.: GZHT9139108402

Certificate Issue Date: Feb 05, 2026

Buyer's Name --
Ref. No. RF605
Brand --
Manufacturer --

We hereby declare that the product category (group) above has been tested by Intertek and meets the requirements of ASTM Specification ASTM F2413-24 as tested in accordance with ASTM Test Methods F2412-24 list the safety hazard(s) tested below.

Tests List:

Protective Toe Impact Resistance (I)
Protective Toe Compression Resistance (C)
Puncture Resistance Footwear (PR)

The test results are given in our report No. GZHT91391084, date Feb 05, 2026

Note:

1. This declaration applies to the particular sample tested and to the specific tests carried out as dated and detailed in the report(s) referenced above.

Approved By:

Intertek Testing Services Shenzhen
Limited, Guangzhou Branch



Guiliang Dong
Senior Lab Manager

Intertek Testing Services Shenzhen Limited, Guangzhou Branch

Page 1/1

Room 401/501/601/701-1/801/901/1003, No. 8, East BaoYing Road
Huangpu District, Guangzhou 510730

深圳天祥质量技术服务有限公司广州分公司

广州市黄埔区保盈东路8号401房、501房、601房、701房-1、801房、901房、1003房
Tel: +86 020-28209114 Postcode:510730

www.intertek.com